


6-31-12W

Company- FRED B. ANSCHUTZ
 Farm- Gress No. 1

SEC. 6 T. 31 R. 12W
 C SE SW

Total Depth. 4668
 Comm. 6-12-64 Comp. 6-30-64
 Shot or Treated.
 Contractor. Terrell Drlg.
 Issued. 9-26-64

County Barber
 KANSAS



Elevation. 1697' KB

Production. 5,600,000 LFG

CASING:

8" 211' cem w/ 177 sx
 4" 3778'

Figures Indicate Bottom of Formations.

rock	38
shale & rock	60
shale & shells	251
red bed & shale	650
hard shale w/ lime strks	805
shale w/ Gyp strks	1175
shale w/ lime strks	1585
lime & shale	1710
lime	2650
shale & lime	2715
lime & shale	3005
shale & lime	3185
lime & shale	3396
lime	3573
Heebner	3580
lime, shale & sand	3658
Douglas	3660
lime & shale	3805
lime	4208
shale & lime	4263
lime & chert	4295
lime	4313
cherty lime & shale	4354
lime	4540
sand-hard	4548
lime & sand	4571
lime	4630
shale, sand & lime	4668 RTD
Total Depth	

TOPS: SCOUT

Heebner	3571
Toronto	3586
Douglas shale	3600
Douglas sand	3627-52
Brown lime	3752
Lansing	3765
Base Kansas City	4188
Reworked Mississippi (smp)	4246
Mississippi chert	4266
Mississippi lime	4288
Kinderhook	4332
Viola	4434
Simpson	4524
Simpson dand	4538
Arbuckle	4628