
Company- PEEL-HARDMAN OIL OPERATORS, ETAL SEC. 32 T. 31 R. 13W
Farm- Brooks No. 1 NW NW SE

32-31-13W

Total Depth. 4840'
Comm. 4-25-62 Comp. 5-15-62
Shot or Treated.
Contractor. Peel Brothers, Inc.
Issued. 12-29-62

County Barber
KANSAS



CASING:
13 3/8" 210' cem. w/200 sx.
5 1/2" 4449' cem.

Elevation. 1651' DF

Production. 7,400,000 CFG

Figures Indicate Bottom of Formations.

shale	340
shale & shells	1700
shale & lime	3155
lime	3330
shale & lime	3560
lime	3615
shale & lime	3770
sand	3771
shale & lime	3865
lime	4007
lime & chert	4050
lime	4326
lime & chert	4365
lime	4470
lime & chert	4496
lime	4560
lime & shale	4610
lime	4670
lime & chert	4702
lime & sand	4740
sand	4780
lime & shale	4820
lime	4840
Total Depth	

TOPS: WELEX	
Heebner	3666
Douglas Sand	3731
Brown Lime	3851
Lansing	3861
Massey Zone	4316
Mississippi	4369
Viola	4605
Simpson Shale	4706
Simpson Sand (Scout)	4732
Arbuckle	4808

DST #1 3727-3771' Op 28 min. Shut in 30"/30". Gas to surface in 4 min. Gauged 2630 MCFG/4 min., 4640 MCFG/8 min., 5210 MCFG/10 min. Sprayed mud after 10 min. & unable to gauge further. Rec. 100' salt water. BHP 1476#/1466#. FP 797#/1194#.

DST #2 4309-4326' Weak blow for 5 min. Flushed tool w/no help to blow. Shut in 30"/30". Rec. 150' mud. BHP 242#/253#. FP 105#/115#.

DST #3 4363-4388' Weak blow for 25 min. Shut in 30"/30". Rec. 65' mud. BHP 122#/94#. FP 42#/63#.