19-31-32W


WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company. STANOLIND OIL & GAS CO.
Farm. Eubank Gas Unit No. 1

SEC. 19 T. 31 R. 32W
SW SW SW NE
2490' S of NL, 2490' W of EL

Total Depth. 2712
Comm. 10-24-54 Comp. 11-8-54
Shot or Treated.
Contractor.
Issued. 1-8-55

County Seward
KANSAS



Elevation. 2869 DF

CASING:

8 5/8 @ 599' w/ 400 sx cmt.
5 1/2 @ 2675' w/ 800 sx cmt.

Production. 8,669,000 Gas

Figures Indicate Bottom of Formations.

surface sand	272
shale & sand	596
red bed	800
red bed & gyp	1089
red bed & shale	1175
gyp, shale & anhydrite	1702
gyp & shale	1780
shale & anhydrite	1937
anhydrite	2000
anhydrite & shale	2300
anhydrite & lime	2385
lime	2709
dolomite	2712
Total Depth	

TOPS:

Herrington	2632
Krider	2674

Schlumberger ran Gamma Ray & Micro-Log.

Treated:
Krider, 250 gal. DF, 5 gal Petrowet, 2500 gal KHV acid 10%, 1250 gal 7½% acid, w/ 10 gal Petrwet, flushed 2700 gal water.
Herrrington, 250 gal. DF, 5 gal petro-wet, 2500 gal KHV 10% acid, 1250 gal. 7½% acid, 10 gal Petrowet, flushed 2665 gal. water.
All zones 10,000 gal 7½% acid & 15 gal Petroweet.

Perf 6 SPF:
Herrington 2634-40, 2650-60