

2-255W

MAP NO. _____ 2952 GR ELEV 2955 DF 2957 KB
 STATE Kan COUNTY Seward SEC. 7 TWP. 31S RGE. 34W
 OPERATOR Mobil Oil Co. LOC. C SW NW
 WELL NO. 1 FARM NAME Marguerite Rooney Unit FT. FROM _____ LINE _____
 L. Cutter FT. FROM _____ LINE _____
 FR. 12/12/61 SPUD 12/21/61 COMP. 2/27/62

CONT./GEOL. Gabbert Jones Tools.

COMPLETION RECORD
 NAME PRODUCING INTERVAL FROM — TO PERF. W/HOLES TREATMENT RECORD
 a Morrow 5318-28 20 Nat.

b _____

c _____

d Cal P

a I. P. OIL/DIST. 195 BQTR. NW GAS M.C.F.P.D. _____ CHK. _____ HRS. 24

b " " " " " "

c " " " " " "

d _____

D & A ()

SIP# _____ FI TP # _____ FI CP# _____ SIBHP _____

GOR. _____ GR. 43.9 deg. PBTD 4350 TD 5680

CASING - CEMENT RECORD
 SIZE DEPTH W/SAX. SIZE DEPTH W/SAX.

8 5/8" 650 275

5 1/2" 5350 1250

OPERATOR Mobil Oil Co. WELL NO. 1 Marguerite Rooney ELEV. 2957 KB

SAMPLE TOPS	DEPTH	SUB SEA	ELEC. TOPS	DEPTH	SUB SEA
No Sample Tops			DF Tops & Datums		
			Hb	4048	-1091
RTD (St Lou) 5680			Lans	4129	-1172
			KC	4397	1440
			Marm	4802	-1845
			Chero	4962	-2005
			Morr	5294	-2337
			Morr sd	5316	-2359
			Chest Mark	5516	-2559
			St Gen	5608	-2651
			St Lou	5626	-2669
			LTD (St Lou) 5680		-2957

Core #1 (Chest) 5572-5603, R 31' = 15' sh blk, 15' sh & silt blk gry interbed, no sho.

RTD 5680. Log. 5 1/2" @ 5350 w/1250 sx. MICT, CO
 4350 PBTD, 20/5318-28 (Morr) Swb & Flo 168 BNO/16 1/2
 hrs (Nat) + 1 2/10% BS & W, 24/64" ck, FTP 50#,
 (Gr 43.8 deg) State Pot: (8 Hr Pmp Rate) Cal P 195
 BOPD/NW, Gr 43.9 deg, Morr 5318-28. CORR: Well
 was FR in Stevens County, should be Seward. COMP.

LIBERAL ELECTRIC LOG TOPS

615854

2956 KB

Winfield 2640 (+326)

Heebner 4042 (-1086)

Toronto 4068 (-1112)

Lansing 4120 (-1164) 4171 (-1215) Amarillo

Marmaton 4764 (-1808)

Morrow 5296 (-2340) T 202', Tss 14'

"S-2" 5314 (-2358) 14/14 ϕ 195 BO

Chester 5498 (-2542)

Ste. Gen 5608 (-2652)

TD 5680