30 - 31 - 5W


WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company. GENE GOFF
Farm- Moritz No. 1

SEC. 30 T. 31 R. 5W
NE NE NE

Total Depth. 4856
Comm. 2-11-56 Comp. 3-6-56
Shot or Treated.
Contractor. Graybol Oil Corp. (Rig No. 3)
Issued. 4-27-57

County Harper
KANSAS



CASING:
8 5/8" 206' cem w/135 sx.

Elevation. 1364 D.F.

Production. Dry

Figures Indicate Bottom of Formations.

surface	440
shale,red beds,lime	1040
lime,shale	1430
lime,sand	1595
lime	1715
lime,shale	2455
shale,lime,sand	2550
lime, sand	2655
shale,lime	2780
lime,shale,sand	2895
lime,shale	3150
shale	3310
shale, sand	3445
shale	3620
lime	3720
lime sandy,lime	3745
lime	3820
lime,shale	3918
lime	3988
shale,lime	4080
lime	4145
shale,lime	4242
lime	4559
lime,shale	4600
shale	4684
Cored 4684 to	4690
sand	4715
sand,shale	4738
sand	4817
sand,lime	4850
lime	4856
Total Depth	

Tops:

Stalnaker	3598
Lansing	3744
Mississippi	4214
Chatanooga	4582
Simpson	4690
Arbuckle	4806

Drill Stem Tests:
#1 4210-42 Tool open 1 hr. Weak Blow throughout test. Recovered 65' mud.
#2 4682-90 Tool open 3/4 hr. Recovered 946' muddy salt water. IFP 0#, FFP 400#, BHP 1800# shut in 15 min.

Cores:
No 1 4684-4690 Recovered 5'