
PRYOR, LOCKHART & WALKER.
McKowen No. 1.

SEC. 18 T. 32 R. 1W.
NEc SW

Total Depth. 4277
Comm. 7-31-36 Comp. 10-4-36
Shot or Treated.
Contractor. S.S. & W. Drilling Co.
Issued. 2-13-37

County Sumner.



Elevation. 1278

CASING.

12½" 416' 8¼" 3738

Production. DRY.

Figures Indicate Bottom of Formations.

shale and lime shells	378	
shale and lime	539	
lime shells and shale	750	
lime and shale	1219	
lime shells and shale	1358	
lime and shale	1480	
sdy shale	1644	
shale and shells	1740	
shale and lime	1796	
lime shells and shale	1941	
lime and shale	2225	
sdy lime	2260	
lime and shale	2395	
lime	2429	
lime and shale	2695	
lime shells and shale	2776	
sdy shale and lime shells	2840	
lime	2875	
lime and shale	2883	
lime	2899	
lime and shale	2933	
shale and lime shells	2978	
shale	3025	
shale and lime shells	3074	
shale	3105	
K.C. lime	3330	
shale and lime	3348	
lime	3355	
shale	3450	
shale and lime	3563	
shale	3738	
chat	3772	show of oil 3746 about 20 bbls.,
lime	3892	and gas and water about 20 bbls wtr.
shale	3895	
lime	3925	
shale	3935	
lime	4078	
shale	4098	
lime hard	4117	
shale	4137	
shale blk	4151	
sand hard	4156	hole reamed to 4156
lime	4184	
shale	4191	
lime	4277	
Total Depth.	1278	