


18-32-1W

Total Depth. 3779'
 Comm. 3-12-38 Comp. 4-16-38
 Shot or Treated.
 Contractor. E.B. Shawver
 Issued. 5-7-38

County. Sumner



CASING:
 12 1/2" 410'
 7 " 3730'

MAY 7 1938

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

surface	10	shale & lime	2872
shale	40	shale & shells	2928
sand	60	shale	3108
shale & shells	378	K.C. lime	3133
lime	385	lime sdy	3152
shale	405	limo	3261
lime	416	shale	3265
shale	427	lime	3335
shale & shells	460	shale & lime	3366
lime	530	shale & shells	3388
shale	550	shale	3446
shale & lime	625	shale & shells	3485
lime brkn	640	shale & lime	3571
shale & lime	870	shale	3575
lime sdy	898	lime	3586
lime	925	shale & lime	3708
shale & lime	962	shale	3738
lime	1000	Corr SLM 3738=3728	
shale	1008	chat	3779
lime	1040	Total Depth.	
shale & lime	1225		
shale	1350		
lime	1375		
shale	1530		
lime	1540		
shale	1705		
lime	1745		
shale & limo	1800		
shale	1817		
sdv limo	1837		
shale & lime	1907		
lime	1920		
shale	1932		
lime	1950		
shale	2010		
lime	2059		
lime & shale	2121		
lime	2127	lime	2490
shale	2192	shale & shells	2520
lime	2235	lime	2541
shale	2245	shale	2693
lime	2265	shale & shells	2718
shale	2280	shale	2760
lime	2300	sdv shale & lime	2826
shale	2345	shale sdy	2830
lime	2376	sdv lime	2838
shale	2470		