
Company STELBAR OIL CORPORATION et al
Farm O'Hara No. 2

SEC. 18 T. 32 R. 1W
SWc NE NW

18-32-1W

County Sumner

KANSAS



Total Depth. 4231 PBTD 3850
Comm. 7-19-55 Comp. 8-4-55
Shot or Treated.
Contractor. Stelbar Oil Corporation, Inc.
Issued. 11-19-55

Elevation. 1281 DF

Production. 12 BO, 75 BWPD

CASING:
8 5/8 423' w/ 410 sx cmt.
5 1/2 3850' w/ 250 sx cmt.

Figures Indicate Bottom of Formations.

broken lime	757
shale & shells	2195
lime	2353
lime & shale	2710
shale	2755
sand	2864
shale	3101
K. C. lime - drilled	3252
K. C. lime - cored	3266
K. C. lime	3355
shale & lime	3728
Mississippi chert	3740
Mississippi dolomite	3751
Mississippi - cored	3775
Mississippi	4062
shale & lime	4132
Simpson sand	4218
Arbuckle lime	4231
Total Depth	
Plugged back to	3850

SCOUT TOPS:

Kansas City	3099
Mississippi	3728
Simpson	4132
Arbuckle	4216

DST #1: 3114-26, open 2 hrs. rec. 610' gas, 90' O&GCM, IFP 12#, FFP 53#, BHP 1050#/20 min.

DST #2: 3288-3313, open 1 hr. gas to surf. 30 min. rec. 230' oil, 60' HOCM, IFP 1#, FFP 100#, BHP 1250#/20 min.

DST #3: 3740-75, open 1 hr. gas to surf. 20 min. rec. 100' drlg. mud. IFP 60#, FFP 90#, BHP 1465#/20 min.

DST #4: 4133-38, open 2 hrs. rec. 180' muddy SW w/ scum oil, IFP 12#, FFP 28#, BHP 1198#/20 min.

PB to 3350 & set plug. Perf. 46/3255-62, HFU 100' overnight, mostly wtr. Acid w/ 500 gal mud acid. Swbd. 20 BPH, mostly wtr. Sqzd. w/ 100 sx cmt. Perf. 5 SPF 3254-61, Acid. w/ 500 gal mud acid. Swbd. 2½ to 3 BPH (1 BO-1½ to 22 BW)