

14-32-11W

WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company: Beardmore Drilling Co.,
Farm: Stewart "C" No. 3

SEC. 14 T. 32 R. 11W
NE SW SW

Total Depth. 3633'

Comm. 10-4-57

Comp. 10-13-57


Shot or Treated.

Contractor: Beardmore Drilling Company

Issued: 12-21-57

County Barber

KANSAS



Elevation. 1514 DE.

Production. Dry

Figures indicate Bottom of Formations.

sand	80
red bed shale & shells	214
shale & lime	1325
shale & lime	2440
shale & lime	3000
shale & lime	3230
shale & lime	3530
shale & lime	3575
shale & lime	3633 RTD
Total Rotary Depth	

TOPS:

Snyderville Sand 3579

Drill Stem Test:

- #1 3583-3597 Shut in 20 mins., open tool, good blow, gas in 50 min. no gauge, open 1 hr. shut in 20 min. Rec. 100' gas cut mud, 1320' muddy gassy wtr. with oil scum. IBHP 1352, FBHP 915, IF 165, FF 560.
- #2 3622-3633 Shut in 20 min., open 1 hr. shut in 20 min., weak blow. Rec. 30' of mud; no flow pressures. IBHP failed, FBHP 180#.

Core:

- #1 3575-3597 Recovered 22'
- #2 3595-3633 Rec. 38' Sand 3597-3599, Shale 3599-3620, Cherty Limestone with show of heavy black oil 3620-3633.