

481-28-08 FILL IN WELL LOG AS REQUIRED:

Show all important zones of porosity and contents thereof; cased intervals, and all drill-loss tests, including depth interval tested, casing used, time test open, flowing and shut-in pressures, and recoveries.

SHOW GEOLOGICAL MARKERS, LOSS RUN, OR OTHER DESCRIPTIVE INFORMATION.

FORMATION DESCRIPTION, CONTENTS, ETC.	TOP	BOTTOM	NAME	DEPTH
DST #1, 4500-20' (Miss.): misrun, pkr. failure.			LOG TOPS	
			Herington	2120 -326
			Onaga Sh	2946 -1152
			Wabaunsee	2998 -1204
			Stotler	3147 -1353
			Topeka	3410 -1616
			Elgin Sh	3734 -1940
			Heebner	3844 -2050
			Doug. Sh	3887 -2093
			L. Doug. Sd	3999 -2205
			Iatan	4026 -2232
			Lans.	4032 -2238
			Swope	4368 -2574
			Hertha	4414 -20
			B/K.C.	4435 -2641
			Marm.	4444 -2650
			Miss.	4506 -2712
			RTD	4630
			LTD	4628
			Ran O.H. Logs	

Report of all strings set— surface, intermediate, production, etc. **CASING RECORD (New) or (Used)**

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs./ft.	Setting depth	Type cement	Seals	Type and percent additives
Conductor	14"	10-3/4"	32#	320'		200 100	lite Class "H"
Surface	new	8-5/8"	24#	1133'		300	RFC

LINER RECORD

PERFORATION RECORD

Top, ft.	Bottom, ft.	Seals cement	Shots per ft.	Size & type	Depth interval
N/A	N/A	N/A.	N/A	N/A	N/A

TUBING RECORD

Size	Setting depth	Porter set of
N/A	N/A	N/A