36-32-23W

WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
503 East Murdock, Wichita, Kansas

Company. STANOLIND OIL & GAS CO.
Farm. Truman C. York No. 1

SEC. 36 T. 32 R. 23W
CNW SW
1980' N. of SL 1980' W. of EL

County Clark
KANSAS

Total Depth. 4800
Comm. 11-26-51 Comp. 2-1-52
Shot or Treated.
Contractor.
Issued. 3-29-52

CASING:
13 3/8" 253' cem. w/500 sx
10 3/4" 573' cem. w/241 sx
5 1/2" 4775' cem. w/300 sx

Elevation. 2016 RDB
2014 (Gnd)
Production. 163 BO

Figures Indicate Bottom of Formations.

surface sand	160
red bed, shale	255
red bed	435
shale	442
red bed	455
red bed, shale	1045
shale, shells	1175
lime, shale	1585
red bed	1610
shale, shells	1990
lime, shale	2190
lime	2400
sandy lime	2490
lime	2705
lime, shale	2782
shale	2825
shale, sand	2865
lime, shale	3165
lime, sand	3205
lime, sand, shale	3270
lime, shale	3673
lime	3680
lime, shale	3930
shale	4010
lime, shale	4380
shale	4387
DSE. lime w/shale strks	4431
dse. lime w/very lgt oil shows	4448
lime, shale strks, oil shows	4498
lime, shale no shows	4638
sft lime, small gas show	4678
lime, oil show	4688
lime, chert	4725
lime	4759
lime, chert	4778
lime	4800
Total Depth	

Tops:
Lansing 4387 - 4800

Ran Schlumberger Elec. Log to TD
Total Depth
By Schlumberger 4800
By Rotary Drill 4800
Plugged back to 4703' in Lansing formation
Perforated: Zone 4682-4683
Acidized w/500 gal. acid tested 7 BFPH 3% wtr. & 3000 MCF gas per day
Completed as a Lansing producer at PBTD