


WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY  
508 East Murdock, Wichita, Kansas

Company- STANOLIND OIL & GAS CO.  
Farm- Jarrett Gas Unit No. 1

SEC. 4 T. 32 R. 33W  
NE NE NE SW  
2490 N of SL & 2490 E of WL  
County Seward SW  $\frac{1}{4}$   
KANSAS



Total Depth. 2697  
Comm. 3-16-54 Comp. 4-8-54  
Shot or Treated.  
Contractor.  
Issued. 8-28-54

Elevation. 2859 D.F.

Production. 1,063,000 gas

CASING:

8 5/8" 605 cem. w/400 sx.  
5 1/2" 2665 cem. w/800 sx.

Figures Indicate Bottom of Formations.

surface clay, shale	130
sand, shale	535
redbed	850
redbed, shale	1630
salt, redbed	1700
redbed	1855
shale	2210
shale, lime	2375
lime	2440
shale, lime	2620
lime	2665
lime, shale	2697
Total Depth	

Tops:

Herrington	2622
Krider	2665

Ran 1 1/4" tubing set @ 2693.  
Schlumberger ran Gamma Ray & Microlog.

Lane Wells perf. w/6 shots per ft. as follows:  
Herrington 2622-26, 2632-34, 2636-41, 2645-48.

Halliburton az as follows:  
Krider w/2500 gal. 15%.  
Herrington w/2000 gal 15%.  
All zones w/11,000 gal 7 1/2%.

Halliburton acid fraced as follows:  
Set packers at 2615-2657. Acidfraced w/2000 gal gel 7 1/2% w/4000# sand, 250 gal diesel w/5 gal Morflo, 150 gal diesel spacer, 1000 gal 7 1/2% w/10 gal Morflo, flushed w/600 gal. wtr.