

19 - 32 - 33W


WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY  
508 East Murdock, Wichita, Kansas

Company- CABOT CARBON CORPORATION.  
Farm- Griffith "A" No. 1

SEC. 19 T. 32 R. 33W  
Approx. SW NE NE  
1250' FNL & 1250' FEL

Total Depth. 2596' DTD 2544' LTD  
Comm. 6-25-58 Comp. 9-2-58  
Shot or Treated.  
Contractor. J. M. Johnson Drilling Co.  
Issued. 5-30-59

County Seward  
KANSAS



Elevation. 2718' KB  
Production. Dry

CASING:

3 5/8" @ 553' w/300 sx.  
4 1/2" @ 2555' w/200 sx.

Figures indicate Bottom of Formations.

sand & gravel	120
red shale	500
red shale & gyp	860
gyp & shells	980
red sandy shale	1505
Anhydrite	1577
red & gray shale	2085
anhydrite & dolomite	2440
dolomite	2555
red & gray shale	2562
dolomite	2596
Total Depth (Driller's)	

Log Total Depth 2544'

TOPS:

Herington	2440
Upper Krider Dolomite	2474
Lower Krider	2555
Winfield Dolomite	2596

PERFORATIONS:

Krider

2455 to 2474, 76 holes, 4 SPF  
2482 to 2519, 148 holes, 4 SPF  
2526 yo 3550, 96 holes, 4 SPF