

29-32-33W

## KANSAS WELL LOG BUREAU --- KANSAS GEOLOGICAL SOCIETY

508 EAST MURDOCK - WICHITA, KANSAS

COMPANY CABOT CARBON CO.

SEC. 29 T. 32 R. 33W

FARM Naden


NO. 1

LOC. CN/2 3/2 NW

TOTAL DEPTH 2568'  
 COMM. 10-15-50  
 SHOT OR TREATED  
 CONTRACTOR  
 ISSUED 3-3-51

COMP. 11-15-50

COUNTY Seward



## CASING

10 3/4" 407' cem. w/250 SX  
 7" 2504' cem. w/750 SX  
 5 1/2" 86' liner

ELEVATION

2757.84  
2770 Ind.

PRODUCTION I.P.A. 10,608,000  
 gas

FIGURES INDICATE BOTTOM OF FORMATIONS

|                       |      |
|-----------------------|------|
| surface soil          | 10   |
| sand, clay, gravel    | 290  |
| clay, red bed         | 415  |
| red bed, sand         | 1550 |
| red bed, gyp          | 1560 |
| gyp, shale            | 1700 |
| gyp, red bed          | 1855 |
| anhydrite, gyp, shale | 1950 |
| shale, shells         | 2070 |
| anhydrite, shale      | 2205 |
| lime, shale           | 2280 |
| lime                  | 2355 |
| anhydrite             | 2435 |
| lime                  | 2512 |
| lime broken           | 2517 |
| shale                 | 2519 |
| lime broken           | 2530 |
| dolomite              | 2568 |
| Total Depth           |      |

Scout Tops:  
 Herrington 2500

Total Acid 14,000 - 15%

Taps:  
 Herr  
 Upper Kri  
 Lower Kri

2500  
 2534  
 2558