

32-32-33W


KANSAS WELL LOG BUREAU---KANSAS GEOLOGICAL SOCIETY
508 EAST MURDOCK - WICHITA, KANSAS

COMPANY CABOT CARBON COMPANY
FARM Fischer NO. 1

SEC. 32 T. 32 R. 33W
LOC. SE SE NW
330' N & W of center

TOTAL DEPTH 2653
COMM. 11-3-50 COMP. 12-23-50
SHOT OR TREATED Acid 16,000 gals.
CONTRACTOR Hills & Hills
ISSUED 3-24-51

COUNTY Seward



CASING

10 3/4" 460' cem w/250 sx
7" 2574' cem w/750 sx
5 1/2 liner 706' cem w/ 38 sx

ELEVATION 2843.14
2845.5nd.
PRODUCTION I.P.A. 888,000 gas

FIGURES INDICATE BOTTOM OF FORMATIONS

sand, gravel 0-435
red rock 470
red rock, gyp, shells 875
shells, red rock 1005
anhydrite, shale 1020
sand, red rock, shale 1420
shale, gyp 1650
shale, gyp, anhydrite, shells 1880
shale, anhydrite 2050
anhydrite 2160
shale blue, gyp, anh. 2265
shale, anhydrite 2325
anhydrite 2390
shale, anhydrite 2515
shale, anhydrite, dolomite 2585
lime, shale 2640
dolomite 2653
Total Depth

Layers:
Herr 2565
Upper Tri 2590
Lower Tri 2610
Winif 2650

Scout Tops:
Herrington 2565
Winfield 2650
Rock Pressure 434.5