
WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY 33-32-7W
508 East Murdock, Wichita, Kansas

Company- SINCLAIR OIL CO.
Farm- George W. Sechler No. 1

SEC. 33 T. 32 R. 7W
NE NE NE
330 fr N & 330 fr EL NE/4

Total Depth. 5027
Comm. 9-10-54 Comp. 10-7-54
Shot or Treated.
Contractor. Adkins Drlg.
Issued. 12-18-54

County Harper
KANSAS



Elevation. 1405 surf,

Production. 64 BO & 504 BW

CASING:
10 3/4" 280 cem. w/200 sx.
7" . 5025 cem. w/250 sx.

Figures Indicate Bottom of Formations.

| | |
|---|---|
| clay & shells | 30 |
| red bed & shells | 281 |
| red bed & shale | 905 |
| sand, shale & shells | 1330 |
| shale & shells | 1510 |
| shale & lime | 2023 |
| lime (Ft. Riley) | 2045 |
| shale & lime | 2800 |
| sdy lime | 2945 |
| shale & lime | 3383 |
| shale | 3430 |
| shale & lime | 3588 |
| shale & sdy lime | 3685 |
| sdy lime | 3708 |
| shale | 3783 |
| shale & lime | 3912 |
| lime | 4004 |
| shale & lime | 4172 |
| lime & shale | 4421 |
| lime | 4505 |
| lime & shale | 4546 |
| lime | 4708 |
| shale & lime | 4742 |
| shale | 4820 |
| cored | 4835 |
| cored | 4845 |
| cored | 4855 |
| lime | 4907 |
| shale & lime | 5014 |
| lime & shale | 5027 |
| Total Depth | |

| Tops: Schlumberger | G.L. |
|---|---|
| Stalnaker | 3608 |
| Kansas City | 3883 |
| Mississippian | 4448 |
| Kinderhook | 4719 |
| Chattanooga | 4797 |
| Viola | 4823 |
| Simpson | 4842 |
| Arbuckle | 5004 |

Sch. T.D. 5028

Ran Schlumberger & Lane Wells.

3 cores: 4821-36, 4836-46, 4846-56.

Perf: 24 holes 4842-4844
16 " 4839-4841
18 " 4841-4843

Acid: 10-11-54 4842-4844 750 gal. 184 BW
Mud acid by Dowell. Prod. after acid: 64 BO & 504 BW in 21 hrs.
10-16-54 4839-4841 250 gal. 191 BW
mud acid by Dowell. Prod. 298 BW no oil or gas
10-21-54 4841-4843 100 gal. 123 BW
mud acid by Halliburton. Prod. suspended.

D.S.T. 9-26-54 4452-4474 tool open 90 min. 17# flowing press 33 shut-in Rec. 80 mud and 480 gas (?)
9-27-54 4474-4505 tool open 60 mins. Flowing press 34#, 138 shut-in Rec. 60' wtr & 360 gas & oil (?).
10-1-54 4823-4836 tool open 90 mins. 15# flowing press 32 shut-in rec. 60' gassy mud
10-2-54 4836-4846 tool open 180 mins. Flowing press. 30, shut-in 120 Rec. 45 oil & 270 gas & oil cut mud.
10-4-54 4846-4856 tool open 180 mins. Rec. 4135
10-7-54 5004-5027 tool open 180 mins. flowing 30# shut-in 640 Rec. 1980