

WELL LOG BUREAU -- KANSAS GEOLOGICAL SOCIETY
412 Union National Bk. Bldg., Wichita, Kansas

17-33-12W

Company - SKELLY OIL CO.
Farm - Boggs "C"

No. 2

SEC. 17 T. 33 R. 12 W
SEc SE
330' FEL & 330' FSL SE $\frac{1}{4}$

Total Depth. 4888' SLM

Comm. 2-8-47


Comp. 3-12-47

Shot or Treated.

Contractor. H & T Drlg. Co.

Issued. 7-5-47

County. Barber
KANSAS



CASING:

13 3/8" 216' Com. w/200 sx.
8 5/8" 1645' Com. w/400 sx.
5 1/2" 4851' Com. w/200 sx.

Elevation. 1528 feet

Production. Pot. 2518 BO, BHP

Figures Indicate Bottom of Formations.

surface soil & red
bed
red bed, sand & shale
red bed & shale
limo & shale
shale & shells
shale
limo & shale
salt
shale & limo
sand & limo
limo
shale
shale & limo
shale
limo & shale
shale & limo sdy
shale
shale & limo
limo
limo & shale
limo
shale
shale & limo
shale
limo
shale
lime
lime & shale
lime & chert
lime gy coarsely
xlyn
dolomite gy sdy &
shale sdy, med hrd
no sat. or por.
sand gy shaley &
dolomite, no por.
or sat.

Tops:
0-216 Lansing Lime 3867
650 Mississippi Lime 4450
750 Misener Sand 4725
1235 Viola Lime 4730
1345 Simpson Series 4831 SLM
1365 Simpson Sand 4851 SLM
1485
1620
1646
1740
2170
2190
3370
3560
3725
3785
3825
3975
4085
4120
4325
4370
4420
4460
4475
4560
4575
4630
4725
4755
4785
4810
4828
4840
4848

sand sft brwn por. &
sat. 4860
sand med hrd brwn, med.
por. & sat. 4867
sand med sft brwn, por.
& sat. 4876
sand med hrd gy sand,
no por. or stain 4881
sand hrd gy, no por.
or sat. 4885
SLM Corr. 4885-4888'
Total Depth 4888 SLM
4848-60' Por. & sat.
4860-67' Med. por. & sat.
4867-76' Por. & sat.
4876-81' No. por. or stain.