

BARBARA OIL CO.
B.E. Holmes "A" No. 4.

SEC. 15 T. 33 R. 13W
CWL SE
440' E CWL SE $\frac{1}{4}$

Total Depth. 4870'
Comm. 12-10-40 Comp. 1-25-41
Shot or Treated.
Contractor. S.A. Springer
Issued. 3-1-41

County. Barbor



CASING:
10" 300'
7" 4825'

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

shale red	50	lime	4385
red rock & shale	550	shale & lime	4415
red rock & gyp	850	lime	4450
red rock & shells	965	lime hrd	4480
shale & shells	1140	shale & lime	4495
shale blue & shells	1280	lime cherty	4544
shale & shells	1480	shale	4555
shale, gyp, & salt	1605	lime chatty	4590
shale & gyp	1810	shale	4620
lime	1820	shale & lime	4680
shale & lime	1925	lime	4685
shale & gyp	1980	lime hrd	4725
lime	2045	lime	4740
shale & lime	2215	shale gy	4760
shale	2225	shale & lime	4775
lime	2370	lime	4785
shale sticky	2400	shale	4790
shale & lime	2410	lime	4805
lime shells & shale	2470	lime blk	4815
shale sticky & lime	2510	shale blk	4825
lime brkn	2540	lime Viola	4870
lime	2560	Total Depth.	
shale & lime	2605		
lime brkn sdy	2620		
shale sticky	2650		
shale	2690		
lime	2700		
shale & shells	2765		
shale	2785		
lime brkn	2820		
lime brkn & shale sticky	2875		
shale & lime	2900		
shale	2945		
shale & lime shells	3025		
shale & lime	3145		
lime	3470		
shale	3505		
shale & lime	3570		
shale	3620		
shale sdy	3645		
shale	3665		
shale & lime	3755		
shale	3800		
shale & lime	3820		
slate	3840		
shale	3870		
shale hrd	3885		
shale sdy	3941		
Core #1	3959		
Core #2	3976		
lime	4210		
lime brkn	4225		
lime sdy	4235		
lime	4245		
lime sdy	4255		
lime	4290		
shale & lime	4295		
slate & lime	4335		
shale & lime	4340		