


BARBARA OIL CO.
Thompson No. 2-B.

SEC. 16
Cen NE $\frac{1}{4}$

T. 33 R. 13W

Total Depth. 4958'
Comm. 9-7-39 Comp. 10-23-39
Shot or Treated.
Contractor. Springrose Drlg.Co.
Issued. 12-30-39

County. Barber



CASING:
10" 282'
7" 4877'

Elevation.

Production. 18,000,000 Gas

Figures Indicate Bottom of Formations.

red rock & gyp shells	282	lime brkn	4145
rod rock, shale, gyp	900	lime brown hrd	4165
red shale & gyp	975	lime brkn	4175
limo shells & shale	1190	lime hrd	4195
shale & shells	1470	lime	4240
shale & salt	1625	lime sdy	4260
shale & gyp	1800	lime	4365
shale & limo	1950	lime hrd	4380
gyp	1965	lime	4395
shale & gyp	2130	shale & lime	4405
shale & lime	2240	lime	4430
sdv lime	2270	lime brkn	4450
shale	2280	lime	4485
shale & lime	2350	lime brkn	4490
sdv lime	2370	lime chaty	4497
lime	2395	lime brkn	4515
shale & lime	2420	lime brown	4527
shale	2450	shale gy	4535
red rock	2460	chat & lime	4555
lime brkn	2515	shale & lime	4568
shale & lime	2585	lime chaty	4577
shale sticky	2610	shale	4590
shale blue	2675	shale & lime	4595
shale	2780	lime & chat	4615
shale & lime	2845	chat, gas & sand	4679
shale sticky	2940	shale gy	4683
shale & lime	3010	lime shells & shale	4710
lime brkn	3070	shale sticky & lime	4730
shale	3090	shale sticky	4770
shale blue	3140	lime	4775
shale sticky	3175	lime hrd	4795
shale & lime	3215	lime	4825
lime	3235	shale & lime	4865
shale & lime	3265	shale blk	4879
lime	3410	sand	4889
lime brkn	3450	slate blk	4915
lime	3490	lime	4958
lime brkn	3500	Total Depth.	
lime	3530		
shale	3560		
shale gy dk hd	3575	Casing perforated 4606-75	
shale brkn	3580		
shale hrd	3585		
shale	3615		
shale sticky	3700		
shale	3765		
shale sticky & lime	3775		
lime shells & shale	3850		
shale & lime	3930		
sdv lime	3975		
lime	3985		
lime brkn	4050		
coring	4065		
slate blk hrd	4065		
brkn shale & sdv lime	4068		
coring	4068		
brkn sdv lime & shale	4078		
brkn sdv lime	4082		
brkn lime	4085		
lime hrd K.C.	4086		
lime	4125		