


16-33-13W

BARBARA OIL COMPANY
Thompson No. 1-C.

SEC. 16 T. 33 R. 13W
Cen SW $\frac{1}{4}$

Total Depth. 4647'
Comm. 3-18-39 Comp. 4-24-39
Shot or Treated.
Contractor. Springrose Drlg. Co.
Issued. 6-3-39

County. Barber



CASING :
10" 300'
7" 4577'

Elevation.

Production. 21,500,000 Gas

Figures Indicate Bottom of Formations.

surface	300	lime K.C.	4115
red rock & gyp	400	lime	4155
red rock, gyp, shale	810	lime hrd	4195
shale red	930	lime	4215
shale grey & gyp	1150	lime brk.	4240
shale & gyp	1245	sdv lime hrd	4255
shale & salt	1260	lime brk.	4310
shale & gyp shells	1290	lime	4325
shale sticky	1310	lime brk.	4340
shale & shells	1400	lime	4345
shale & salt	1445	lime hrd	4365
salt & shells	1595	shale & lime	4370
gyp, shale, salt	1670	shale	4375
lime & shale	1810	lime hrd	4395
lime, shale, gyp	1875	lime	4405
shale & gyp	1930	lime brk.	4453
shale & shells	1960	lime blk	4465
lime	2045	shale & lime	4475
shale & gyp	2100	lime brk.	4495
shale & lime	2235	lime & shale	4541
sdv lime & shale	2330	chatty lime	4577
lime	2385	chat	4595
shale & lime	2440	shale	4599
lime	2490	ohert	4608
shale & lime	2740	chat hrd	4612
lime	2765	chat	4618
shale sticky & lime		chat & lime	4621
shells	2865	chat hrd	4628
shale sticky	2900	chat sdv	4631
lime brk.	2925	chat & lime	4636
lime shells & shale		lime hrd	4639
sticky	3040	chat & shale	4647
shale & lime	3095	Total Depth.	
lime shells & shale			
sticky	3130		
shale & lime	3180		
lime	3340		
shale sticky	3355		
lime brk.	3380		
lime	3470		
sdv lime brk.	3490		
lime	3510		
sdv lime brk.	3515		
lime	3525		
shale sticky	3545		
shale	3590		
shale sticky	3625		
shale	3775		
shale & lime	3800		
shale	3900		
shale sdv	3920		
shale & lime	3980		
shale sticky & lime	4015		
coring-shale	4031		
coring-sdv lime	4035		
coring-sand	4040		
coring-shale blk	4049		
shale	4062		
lime brk.	4065		