


SINCLAIR PRAIRIE OIL CO.
 Exchange Bank No. 1.

SEC.27 T.33 R. 19 W
 SEc SW
 330'fr S & E Lines SW $\frac{1}{4}$

Total Depth. 6525'
 Comm. 2-15-42 Comp. 6-29-42
 Shot or Treated.
 Contractor. Harbar Drlg.Co.
 Issued. 6-20-42

County. Comanche



CASING:
 20" 32 $\frac{1}{2}$ ' Cem.
 13" 451' Cem.

Elevation.

Production. Dry

Figures Indicate Bottom of Formations

surface clay	40	lime (cored 5941-6013)	5941
sand	70	lime (cored 5941-6095)	6041
red bed	245	lime (cored 6106-6112)	6106
sand (19" hole)	288	lime & chert	6123
red bed	420	chert	6128
lime (17 $\frac{3}{4}$ " hole)	465	lime & chert	6138
red bed & shells	1265	chert	6144
(9" hole)		lime & chert	6152
lime	1290	chert	6157
salt & shale	1485	lime & chert	6194
shale & shells	1600	lime	6206
lime	1610	chert	6208
shale & lime shells	2000	lime & chert	6213
lime & shale	2290	chert	6217
lime	2580	lime (cored 6219-31)	6219
lime & shale	2720	chert	6239
lime	2795	lime & chert	6243
lime & chert	2815	chert	6251
lime	3035	lime & chert	6257
lime & shale	3080	chert	6262
lime	3105	lime & chert	6274
lime & shale	3250	cored 6274-90	
shale	3275	lost circulation & cemented	
lime	3300	off	
lime & shale	3420	lime	6329
lime shells shale	3475	lime & chert	6338
lime & shale	3645	cored 6338-92	
lime	3700	no records 6392-6426	
lime & shale	3775	cored 6426-6478	
lime	3895	chert	6480
lime & shale	4160	lime	6491
shale & shells	4275	cored 6491-6509	
lime and shale	4305	lime	6525
lime	4370	Total Depth.	
lime & shale	4415		
lime	4445	Ran Schlumberger test	
lime & shale	4550	Dry hole	
lime	4860	Plgd and abnd 6-5-42	
lime & chert	4875		
lime sft	4896		
lime	4950		
lime & shale	4985		
lime (cored 5120-25)	5121		
lime & shale	5125		
lime	5375		
(cored 5375-5465)			
lime	5680		
lime-chert	5684		
lime	5690		
lime & chert	5759		
chert	5761		
lime & chert	5768		
lime	5775		
lime & chert	5786		
chert	5790		
lime & chert	5817		
lime	5860		
lime & chert	5870		