


State Kansas Field Singler  
 Company Shamrock County meade  
 Farm HEINSON No. 3  
 Sec. 29 Twp. 33S Range 29W

Spot SW SESE  
 Contractor D+M  
 Remarks \_\_\_\_\_



Comm. 9/8/56 Comp. 10-15-56  
 Elev. DF 2629 GL 2615 KB TD 5951 PB \_\_\_\_\_  
 Pay 5886-95

I.P. 393 B.O.P.D. Press. CP800, TP 50  
 Casing Record: 13<sup>3</sup>/<sub>8</sub> 950/900 7" 5953/250  
 20" 10<sup>3</sup>/<sub>4</sub> 5<sup>1</sup>/<sub>2</sub>"  
 16" 8<sup>5</sup>/<sub>8</sub>

| loc   | Sample | Log            |
|---|--------|----------------|
| <del>SEP 1 2</del> <u>SEP 1 2</u> <u>WOC</u>                              |        | Top 4773       |
| <del>SEP 1 9</del> <u>SEP 1 9</u> <u>TTO 3320</u>                         |        | Case 4596      |
| <del>SEP 2 6</del> <u>SEP 2 6</u> <u>4845</u>                             |        | Marm 5268 ✓    |
| <del>OCT 3 0</del> <u>OCT 3 0</u> <u>5827</u>                             |        | Cher 5442      |
| <del>OCT 1 0</del> <u>OCT 1 0</u> <u>5786-5846</u> <u>1450'</u>           |        | at 5546        |
| <u>14' bl sh.</u>   |        | Mor 5790 ✓     |
| <u>8' frag lite gl. ss.</u>   |        | Mor sd 5854-66 |
| <u>4' frag lite crin. ss.</u>   |        | " " 5880-89    |
| <u>12' bl sh.</u>   |        | MISS 5936 ✓    |
| <u>2'8" v. fm gr. lite shly ss</u>  |        |                |
| <u>4" bl sh.</u>  |        |                |
| <u>2'4" green sdy sh.</u>   |        |                |
| <u>8" bl. sh.</u>   |        |                |
| <u>6' v fm gr. lite shly ss.</u>  |        |                |
| <u>5846-70</u> <u>rec 24'</u>   |        |                |
| <u>11' bl sh.</u>   |        |                |
| <u>12' fm gr. ss. to sd par.</u>  |        |                |
| <u>sent to Nat stain.</u>   |        |                |
| <u>6" bl sh. sdy.</u>   |        |                |
| <u>DST 5844-70</u> <u>up 1 1/2 hrs</u> <u>GTS 38"</u> <u>max 9.25 MCF</u> |        |                |
| <u>in 90" rec 60' v hv. OCM.</u> <u>+90' 5li MC oil</u>                   |        |                |
| <u>+300' oil +60' muddy SW. TSP</u> <u>2022/30</u>                        |        |                |
| <u>FP 507122 FBHP</u> <u>1940/30</u>                                      |        |                |

5870-5909 rec. 39'  
7' hl. sh.  
2' hl. sh. adq.  
9' ss. fr. gr. vert. fr. gd. por. stains.  
21' sh.

RTD 5951 Now Schl 5948 from 7" to 5953  
W 250

OCT 17 CO PE 18/5886-95 T @ 5897 A/500M  
swab load, fl 99 BO/Bhr 1/2" ck CP 169 TP 75  
fl 3160 3hr 1/2" ck CP 225 TP 275 WOT

OCT 24 c Test fl 131 BO 8hrs 1/2" ck, CP 200  
TP 50, 24hr rate 393 BO. 634.5

### AMARILLO TOPS

2626 KB

Winfield 2816 (-190)

Heebner 4444 (-1718)

Douglas 4454 (-1858)

Morrow 5790 (-3164)

Sand 5808 (-3182)

Sand 5890 (-3264) T 10', por 10', 393 BOPD

Chester 5936 (-3310)

TD 5948 (-3322)