

34-34-1210  
ACO-1 WELL HISTORY

TYPE

★ AFFIDAVIT OF COMPLETION FORM

ACO-1 WELL HISTORY

SIDE ONE

Two (2) copies of this form shall be filed with the Kansas Corporation Commission, 200 Colorado Derby Building, Wichita, Kansas 67202, within thirty (30) days after the completion of a well, regardless of how the well was completed.

Attach separate letter of request if the information is to be held confidential. If confidential, only file one copy. Information on Side One will be of public record and Side Two will then be held confidential.

Applications must be made on dual completion, commingling, salt water disposal, injection and temporarily abandoned wells.

Attach one copy only wireline logs (i.e. electrical log, sonic log, gamma ray neutron log, etc.). (Rules 82-2-105 & 82-2-125) KCC# (316) 263-3238.

LICENSE # 5041 EXPIRATION DATE 6-30-83

OPERATOR Ram Petroleum Corporation API NO. 15-007-21,012

ADDRESS 1260 KSB&T Bldg. COUNTY Barber

Wichita, Kansas 67202 FIELD Stranathan

\*\* CONTACT PERSON Robt K. Edmiston PROD. FORMATION Mississippi  
PHONE (316) 265-5241

PURCHASER (oil) Koch (gas) KS Gas Supply LEASE Terwort

ADDRESS P.O. Box 2256 Box 300 WELL NO. #4

Wichita, KS 67201 Tulsa, OK 74102 WELL LOCATION SW NE SW

DRILLING Union Drilling 990 Ft. from North Line and

CONTRACTOR ADDRESS 422 Union Center Bldg. 990 Ft. from East Line of

Wichita, Kansas 67202 the SW (Qtr.) SEC 34 TWP 34 RGE 12 W.

PLUGGING CONTRACTOR ADDRESS

WELL PLAT

(Office Use Only)


KCC   
KGS   
SWD/REP   
PLG.

TOTAL DEPTH 4840 PBSD NA

SPUD DATE 11-12-80 DATE COMPLETED 11-21-80

ELEV: GR 1431 DF 1433 KB 1436

DRILLED WITH (CABLE) (ROTARY) (AIR) TOOLS.

DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE

Amount of surface pipe set and cemented 329 DV Tool Used? no

THIS AFFIDAVIT APPLIES TO: (Circle ONE) Oil, Gas, Shut-in Gas, Dry, Disposal, Injection, Temporarily Abandoned, OWWO. Other

ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATIONS PROMULGATED TO REGULATE THE OIL AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH.

A F F I D A V I T

Robt K. Edmiston, being of lawful age, hereby certifies that:

I am the Affiant, and I am familiar with the contents of the foregoing Affidavit. The statements and allegations contained therein are true and correct.

W-57-15-15  
 SIDE TWO  
 OPERATOR Ram Petroleum Corporation

FILL IN WELL LOG AS REQUIRED:

FORMATION DESCRIPTION, CONTENTS, ETC.			TOP	BOTTOM	NAME	DEPTH
Sand & Redbed			0	329	Heebner	3818
Redbed & Shale			329	504	Kansas City	4338
Shale			504	4030	Base Ks. City	4584
Shale & Lime			4030	4279	Cherokee	4720
Lime & Shale			4279	4685	Cherokee Sd.	4745
Lime			4685	4840	Weathered Miss.	4755
RTD				4840	Solid Miss.	4763
					LTD	4838
Drill Stem Test #1 4738-4755 (Cherokee) 30-30-120-90. Weak Blow. Rec. 70' mud. ISIP 64#, FSIP 118#, FP 43-43# Drill Stem Test #2 4754-4790 (Mississippi) 30-30-120-90. Gas to surface/15 min., & Ga. 122,000 cfg. It then decreased to 8,800 cfg/2 hrs. Rec. 3,000' slightly muddy gassy oil. ISIP 1370#, FSIP 1327#, FP 237-688#						

ACID, FRACTURE, SHOT, CEMENT SQUEEZE RECORD

Amount and kind of material used				Depth interval treated	
Acid: 300 gal. 15% Demud, 1 gal. I-2				4763-4773	
Frac: 40,000# sd. (30,000# 20/40 sd., 10,000# 10/20 sd.)				4763-4773	
Date of first production		Producing method (flowing, pumping, gas lift, etc.)		Gravity	
		Pumping		23.0	
RATE OF PRODUCTION 24 HOURS	Oil	Gas	Water	Gas-oil ratio	CFPS
	6 bbls.	54.3 MCF	75 %	9050	
Perforations			20		

\* NOTE: Edmiston Oil Company, Inc., operates this well from the casing point.

--	--	--	--	--

Report of all strings set — surface, intermediate, production, etc. CASING RECORD (New) or (Used)

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
Surface		10-3/4		329	Common	275	2% gel, 3% cc
Production		4-1/2		4839	50/50 Posmix	225	

LINER RECORD

PERFORATION RECORD

Top, ft.	Bottom, ft.	Sacks cement	Shots per ft.	Size & type	Depth interval
TUBING RECORD			2		4763-4773
Size	Setting depth	Packet set at			