

15-007-20276

AUG 28 1974

36-34-13W

KANSAS DRILLERS LOG


State Geological Survey

API No. 15 — 007 — 20276
County Number

S. 36 T. 34 R. 13 W

Loc. 1980 ENL 1980 FEL

County Barber

640 Acres
NLocate well correctly
1455.3

Elev.: Gr.

DF KB 1463.3

Operator

ANDOVER OIL COMPANY

Address 912 Philtower Bldg., Tulsa, Oklahoma

Well No.

#3

Lease Name

B. Sterling "C"

Footage Location

660

feet from (N) (S) line

660

feet from (E) (W) line

Principal Contractor

DaMac Drilling Company

Geologist

Bob Sandridge

Spud Date

9-16-74

Total Depth

4900

P.B.T.D.

4873

Date Completed

10-6-74

Oil Purchaser

CASING RECORD

Report of all strings set — surface, intermediate, production, etc.

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
Surface	12 $\frac{1}{4}$	8 5/8	28	335	Common	280	2% CC
Production	7 7/8	4 $\frac{1}{2}$	10.5	4900	REC	125	1% CC

LINER RECORD

Top, ft.	Bottom, ft.	Sacks cement
----------	-------------	--------------

PERFORATION RECORD

Top, ft.	Bottom, ft.	Sacks cement	Shots per ft.	Size & type	Depth interval
			1 HPF		4802-06
					4808-40

TUBING RECORD

Size	Setting depth	Packer set at
2 3/8		4717

ACID, FRACTURE, SHOT, CEMENT SQUEEZE RECORD

Amount and kind of material used	Depth interval treated
1000 gal. DDS, 1500 gal. 5% HCL. Frac'd with	
40,000 gal. SW, 35,000 20/40 sd. Flushed w/1140 bbls.	

INITIAL PRODUCTION

Date of first production		Producing method (flowing, pumping, gas lift, etc.)		
10-13-74				
RATE OF PRODUCTION PER 24 HOURS	Oil	Gas	Water	Gas-oil ratio
	18 bbls.	MCF	72 bbls.	CFPB
Disposition of gas (vented, used on lease or sold)			Producing interval (s)	

INSTRUCTIONS: As provided in KCC Rule 82-2-125, within 90 days after completion of a well, one completed copy of this Drillers Log shall be transmitted to the State Geological Survey of Kansas, 4150 Monroe Street, Wichita, Kansas 67209. Copies of this form are available from the Conservation Division, State Corporation Commission, 3830 So. Meridian (P.O. Box 17027), Wichita, Kansas 66217. Phone AC 316-522-2206. If confidential custody is desired, please note Rule 82-2-125. Drillers Logs will be on open file in the Oil and Gas Division, State Geological Survey of Kansas, Lawrence, Kansas 66044.

Operator ANDOVER OIL COMPANY		DESIGNATE TYPE OF COMP.: OIL, GAS, DRY HOLE, SWDW, ETC.:
Well No. 3	Lease Name B. Sterling "C"	Oil
S <u>36</u> T <u>34</u> R <u>13</u> ^E _W		

WELL LOG

Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION.

FORMATION DESCRIPTION, CONTENTS, ETC.	TOP	BOTTOM	NAME	DEPTH
Red Bed	0	335		
Shale	335	975		
Shale and Shells	975	1950		
Lime and Shale	1950	2115		
Lime	2115	2480		
Lime and Shale	2480	2680		
Shale and Lim e	2680	2825		
Lime and Shale	2825	3160		
Shale and Lime	3160	3314		
Lime and Shale	3314	3630		
Lime	3630	4190		
Kansas City Lime	4190	4278		
Lime and Shale	4278	4330		
Lime	4330	4410		
Shale and Lime	4410	4490		
Lime	4490	4550		
Lime and Shale	4550	4785		
Lime	4785	4850		
Lime	4850	4900		
R.T.D.	4900'	4900'		

USE ADDITIONAL SHEETS, IF NECESSARY, TO COMPLETE WELL RECORD.

	Signature <i>Bobby Young</i>
	Title Manager Drilling & Operations
	Date January 24, 1975

30-30-100

Sands Drilling Co.

ARM Blanche Sterling

NO. C-3

36-34-13W

SEC. 36

T. 34S

R. 13W

LOC. 1980 FEL 1980 FWL


TOTAL DEPTH 4900'

COUNTY Barber County, Kansas

COMM. 9-16-74

COMP. 9-23-74

CONTRACTOR DaMac Drilling Company, Inc.



CASING 8 5/8" @ 335' w/280 sx.
4 1/2" @ 4900" w/125sx.

ELEVATION

PRODUCTION

FIGURES INDICATE BOTTOM OF FORMATIONS

335'	Red Bed
975'	Shale
1950'	Shale and Shells
2115'	Lime and Shale
2480'	Lime
2680'	Lime and Shale
2825'	Shale and Lime
3160'	Lime and Shale
3314'	Shale and Lime
3630'	Lime and Shale
4190'	Lime
4278'	Kansas City Lime
4330'	Lime and Shale
4410'	Lime
4490'	Shale and Lime
4550'	Lime
4785'	Lime and Shale
4850'	Lime
4900'	Lime
4900'	R.T.D.



State of Kansas }