


State Ks. Field MOHLER
 Company SHAMROCK County MEADE
 Farm ERNEST CORDS No. 1
 Sec. 2 Twp. 34S Range 29 W

Spot NW1/4 NE
 Contractor D & M
 Remarks P.D. 5875



Comm. 8-9-58 Comp. 10/8/58
 Elev. DF 2502GL KB TD 5910 PB
 Pay

I.P. Press.
 Casing Record: 13 3/8 7"
 20" 10 3/4 5 1/2" 5915/25
 16" 8 5/8 1544/800

loc.	Sample	Log
AUG 13 spud, csg, WOC		HR ⁻¹⁹⁰⁶ 4402
AUG 20 φ 3225 ls		Toro ⁻¹⁹³² 4434
stuck & turned off pipes - Rec.		LAN ⁻²⁰³⁸ 4540
		MARM ⁻²⁶⁴² 5197
AUG 28 φ 3871 1st sh		Novinger pay ⁻²⁷⁶⁰ 5262
		Geo ⁻²⁸⁷⁰ 5372
SEP 3 φ 5097 " "		Alpha ⁻²⁹⁸² 5484
SEP 3 φ 5180-5215		FING. ls ⁻³¹⁰² 5604
Rec. 35' -		Mov. ⁻³²²² 5724
1' ls fine		" ss ⁻³²⁴⁴ 5746
6' marl		" ⁻³²⁶¹ 63
4 1/2' sh		Misc ⁻³³⁰⁰ 5802
1 1/2' ls		
16' HASH - bott. 2' bdy xw		
7' ls fine		
€ 5260-8'3' Rec 22'		
22' ls N.S.		
φ 5500 ls		
TD 5722, prep. core		
SEP 10 € 5722-72 Rec 42'		
3' sh ; 3' ls orange		
1' silty ss ; 5' marl		
2' stl ls ; 2' sh pinkish		

611487

3' ls fossil; 4 1/2' ss (no fl. or str)
3' sh pakerchip; 6 1/2' ss odor gas, no fl
9' sh

DST 5725-72 Op. 90", Rec. 750'
xw, no sho gas, ISIP 1970/30"
FP 165-410, FSIP 1505/30"
E 5772-5822 Rec. 50'

5' sh pakerchip
7' ls silty; 3 1/2' sh
4' " IR Aldg wtr; 3' marl
14 1/2' " ; 1' sh; 2 1/2'
1/2' sh; 3' marl; 3' ls tota
RTD 5910, S; 5918

prep casing
SEP 17 DST 5816-5918 Op. 1', gts 15"
Tstn Rec. 110' GCM, ISIP 1535/30"
FP-0, FSIP 1120/30"

~~cas~~ C.O. 5876, G.R.
P/56 '5844-58 2" tbg 5866
MCT, Ac 1000 (7 1/2%), Swd. 7
gals fl./hr (62% ac wtr + 38% new oil)
g. 139 mcf, FCP-100

SEP 24 Ac 2500 + 2500 (7 1/2%), Swbg. Id.
Ac 2100 (8%)
Ac frac. 19 (5%) x 18, KO.
flood H. - 3 1/2' Swd. 15 B. fl./hr.
(95% ld. + 5% new oil)
g. 139 mcf, SI-5', SIP-100
full tbg, Bail 250 gals sand
Swbg. w/ SSG

OCT 1 P/g 4824-26 plus 4856
SQ 48 2420/200

P/g 4806-08 SQ/100
CO cem 4825 perl 60/4806-21,
ran T 4820? A/1000 (15%) subgell,
OCT 8 CO. p60/4804-19

A/1000 (15%) sub Id. + 195 BSW/24 hrs
mat to P+A.

O + A

Shamrock O &G
Ernest Cordes #1
NW NW NE of 2-34-29

AMARILLO TOPS

2504 KB

Heebner 4394 (-1890)

Lansing 4550 (-2046)

Morrow 5725 (-3221) T 77', Tss 20'

"S-2" Sd 5743 (-3239) 14/20, tst'd XW

Chester 5802 (-3298) g 139 MCF / oil