


11-34-20W

County Comanche
KANSAS

Total Depth. 6523'
Comm. 10-18-63 Comp. 11-27-63
Shot or Treated.
Contractor. Patton Drilling
Issued. 2-8-64



Elevation. 1784' DF

Production. Dry

CASING:

13" 42'
8" 531' cem w/250 sx.

Figures Indicate Bottom of Formations.

sand, shle red	793
Anhydrite	1047
red & gray shale	1439
Anhydrite, green-gray & red shale	1591
Anhydrite	2288
Dolomite	2480
limestone, shale	3957
shale	4018
sand	4044
shale	4114
lime, shale	4215
shale	4280
sand	4295
shale	4338
lime, shale	4844
shale	4883
lime, shale	5127
Cherty lime	5290
lime, Dolomite	5700
Chert	6103
Dolomite, chert	6292
Sdy Dolomite, green shale	6404
sand	6431
Dolomite, cherty Dolomite	5620 RTD
Dolomite, Cherty Dolomite ?	5623
Total Depth	

TOPS: LOG

Cimarron Anhydrite	793
Wellington (sample)	1435
Salt (sample)	1570-2070
Herrington (sample)	2290
Winfield	2332
Upper Ft. Riley (sample)	2370
Lower Ft. Riley (sample)	2430
Elgin Zone	3957
Elgin Sand	4018
Heebner	4146
Douglas	4215
Douglas Sand	4280
Lansing	4338
Base Kansas City	4844
Marmaton	4885
Cherokee	5011
Mississippi	5127
Cowley	5700
Viola	6103
Simpson	6292
Arbuckle	6431