

13-34-33W


WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY  
500 East Murdock, Wichita, Kansas

Company- ANADARKO PROD. CO.  
Farm- Eubank "B" No. 4

SEC. 13 T. 34 R. 33W  
C NE SE  
1980' NSL & 1980' EWL

Total Depth. 6370'  
Comm. 3-28-65 Comp. 4-14-65  
Shot or Treated.  
Contractor. Moran Bros., Inc.  
Issued. 6-12-65

County Seward  
KANSAS



Elevation. 2089' GR

Production. Flo. 68.81 BO 4 hrs.

CASING:

8 5/8" 1599' w/900 sx cem.  
4 1/2" 6369' w/130 sx cem.

Figures indicate Bottom of Formations.

surface sand, clay	1000
sand, red bed, gypsum	1600
red bed, anhydrite	2051
Anhdrite, shale	2930
lime	3807
shale, lime	4572
lime	5730
shale, lime	6370
Total Depth	

TOPS: SCOUT

B/Cimarron	1635
Herington	2642
U, Krider	2666
Winfield	2760
Toronto	4354
Jasnign	4488
Morrow	5774
Mississippi	6014
St. Genevieve	6356

OIL OR GAS SANDS OR ZONES

Chester	6288-6290
Chester	6276-6286

PERF: 6288-6290 w/4 shots  
6276-6286 w/20 "

ACIDIZED: 6288-6290 w/250 gals.  
6276-6286 w/1000 "

DEC 21 1987

WICHITA RANGE  
DRILLER'S LOG

13-34-33W *Inc*

WELL NAME: Eubank "B" No. 4; COMPANY OPERATING: Anadarko Production Company  
 ADDRESS of COMPANY: Box 351, Liberal, Kansas

WELL LOCATION: C 1/4 NE 1/4 SE 1/4,  
1980 ft. North of South line,  
1980 ft. East of West line; Sec. 13, Twp. 34S, Rge. 33W, Seward County, Kansas

DRILLING STARTED 3-28, 1965; DRILLING COMPLETED 4-9, 1965  
 WELL COMPLETED 4-14, 1965; WELL CONNECTED \_\_\_\_\_, 19\_\_\_\_

ELEVATION: 2808.9 ft. Ground Level; CHARACTER OF WELL (Oil, Gas, or Dry Hole) Oil

OIL OR GAS SANDS OR ZONES - PERFORATIONS - ACIDIZING AND FRACTURING INFORMATION					
Name	From	To	No. of Shots	Gallons Used	Kind Used
Chester	6288	6290	4	250	15% MC Acid
Chester	6276	6286	20	1000	15% MC Acid

CASING RECORD

Size	Amount Set	Sacks of Cement	Amount Pulled
8-5/8"	1599'	900	
4-1/2"	6369'	130	

FORMATION RECORD

Formation	Top	Bottom	Formation	Top	Bottom
Surface sand & clay	0	1000			
Sand, red bed & gypsum	1000	1600			
Sand bed & anhydrite	1600	2051			
Anhydrite & shale	2051	2930			
Lime	2930	3807			
Shale & lime	3807	4572			
Lime	4572	5730			
Shale & lime	5730	6370			
Total Depth	6370				

RESULTS of INITIAL PRODUCTION TEST: Flowed 68.81 BO in 4 hours.