State Geological Survey
WICHITA BRANCH
KANSAS DRILLERS LOG

IMPORTANT
Kans. Geo. Survey request samples on this well.

15-189-20472
9-34-35W


S. 9 T. 34 R. 35 E/W

API No. 15 — 189 (County) — 20,472 (Number)

Loc. NW NW SE

County Stevens

640 Acres
N



Locate well correctly

Elev.: Gr. 3017

DF _____ KB 3021

Operator
Mohawk Energy Corp.

Address
2401 Fourth Nat'l Bk Bldg. Tulsa, Okla 74119

Well No.	Lease Name
#1	Skinner

Footage Location
330 feet from (N) ~~(S)~~ line 330 feet from ~~(E)~~ (W) line

Principal Contractor	Geologist	
Gabbert-Jones, Inc.	Bob Posey	
Spud Date	**Total Depth**	**P.B.T.D.**
Oct. 2, 1979	6650'	
Date Completed	**Oil Purchaser**	
Oct. 17, 1979	Dry and abandoned	

CASING RECORD

Report of all strings set — surface, intermediate, production, etc.

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
Surface pipe	12-1/4"	8-5/8"	23#	1754'	HOWCO lt. wt. Common	750 150	2% c.c. 3% c.c.

Surface clay - sand	0	500	Heebner	4302	-1281
Redbed-sand-shale	500	1240	Toronto	4332	-1311
Redbed-shale	1240	1554	Lansing	4416	-1395
Redbed-anhy	1554	1754	Marmaton	5136	-2117
Anhy-redbed	1754	1900	Morrow shale	5838	-2817
Shale-anhy	1900	2375	Morrow lower sand zone	6140	-3119
Shale-lime	2375	2444	Chester shale	6193	-3172
Lime-shale	2444	6650	Chester sandy		
		6650			

MOHAWK ENERGY CORPORATION
2401 FOURTH NAT'L BANK BLDG
TULSA, OK 74119
CONTR GABBERT-JONES INC.

#1 SKINNER
9-34-35W
NW NW SE

CTY STEVENS

GEOL BOB POSEY

FIELD SKI

E 3021 KB CM 10/1/79 CARD ISSUED 11/10/79 IP D&A/MISS 10/16/79

API 15-189-20,472

SMP TOPS	DEPTH	DATUM
HEEB	4302	-1281
TOR	4332	-1311
LANS	4416	-1395
MARM	5136	-2115
MRW SH	5838	-2817
L MRW SD	6140	-3119
CHEST SH	6193	-3072
CHEST SD	6406	-3385
STE GEN	6478	-3457
ST L	6540	-3519
RTD	6650	-3629

8-5/8" 1754

NO LOG
DST (1) 6390-6644/45-45-60-60, REC 186' DM, SIP 1817-1823#, FP 161-210/210-226#, HP 3319-3270#, BHT 14°

INDEPENDENT OIL & GAS SERVICE
WICHITA, KANSAS