


J. M. HUBER CORP.
Dunne-Hoffman No. 4.

SEC.7 T.34 R. 37 W
Cen SE $\frac{1}{4}$

Total Depth. 2884'
Comm. 4-11-42 Comp. 5-10-42
Shot or Treated.
Contractor.
Issued. 6-13-42

County. Stevens



CASING:

10 $\frac{3}{4}$ " 606' Cem.
7" 2696' Cem.
5 $\frac{1}{2}$ " liner 235' @ 2884'

Elevation.

Production. 4,500,000 G.

Figures Indicate Bottom of Formations.

surface sand	120
wtr, sand, & gravel	410
sand & red rock	590
red rock	1040
gyp, shale, red rock	1576
shale & gyp shells	1715
sand, lime & shale	1785
sdv lime & shale	1823
shale & anhydrite	1898
shale & lime shells	2134
sand & shale red	2290
shale gy & anhydrite	2350
anhydrite & dolomite	2370
anhydrite & sand	2390
anhydrite & shale red	2400
anhydrite	2600
anhydrite & dolomite	2640
sand & anhydrite	2650
dolomite	2690
shale gy & dolomite	2700
shale red & dolomite	2705
dolomite	2720
silt red & gy	2725
shale red & gy	2730
dolomite	2765
shale red	2770
sand & dolomite	2775
shale red & dolomite	2790
sand & lime	2795
lime	2830
silt & lime	2840
silt gy	2845
lime	2860
limo sdv	2878
limo	2884
Total Depth.	

1st sh gas 2665-75
inc. 2680-85
inc. 2695-2720
inc. 2755-65
inc. 2803-33
4 $\frac{1}{2}$ million

Rotary to 2710'