


KUHN BROS.
Armstrong No. 1.

16-34-37 W
SEC. 16 T. 34 R. 39W
Cen SE $\frac{1}{4}$

Total Depth. 2765'
Comm. 5-14-37 Comp. 6-20-37
Shot or Treated.
Contractor. Kuhn Bros.
Issued. 12-18-37

County. Morton.

DEC 18 1937



Plotted

CASING:

Elevation.

Production. 9,500,000 Gas.

Figures Indicate Bottom of Formations.

Drilled with Rotary Tools;

no log	50	red rock	2728
quick sand, & gravel, shells	328	sdv lime	2760
sand & gravel	562	shale blue	2765
red bed	587	Total Depth.	
red bed	683		
anhydrite	765		
sdv shale & shells	1125		
coarse sand.			
shells & sand	1135		
anhydrite	1217		
red bed & strks shale	1309		
red bed & shale	1350		
sand shell, strks gyp	1590		
gyp	1600		
red bed	1697		
gyp & strks sand hrd	1851		
sand & lime strks hrd	1995		
sand, anhydrite & stks			
of shell	2126		
anhydrite, strks shells	2225		
red bed & sand	2250		
anhydrite	2347		
anhydrite & shale blue	2405		
shale sticky	2433		
anhydrite	2495		
anhydrite, strks blue	2530		
shale & brkn lime,			
hrd shale blue	2575		
premature lime	2590		
anhydrite & shells (layed			
down 4" pipe)	2590		
Standardized at	2590		
Finished laying down D.P.	2590		
shale, lime shells	2600	lime shell	2670
sdv lime	2635	sand red	2675
Inc in gas at 2608		lime	2705
shale blue	2640	Inc in gas flow	2690-2695
red rock	2651	shale blue	2710
shale	2655		
lime shell	2660		
shale red	2663		