


9-66W+

MAP NO. 92SEC. 20 TWP. 34S RGE. 43WSTATE Kans COUNTY Morton App LOC. C SE NWOPERATOR Anadarko Prod. Co. 1780 FT. FROM N LINEWELL NO. 1 FARM NAME Interstate "F" (Twin) 1980 FT. FROM W LINEInterstate ELEV. 3502 GR. 3508 E DF 3510 E.K.B.6/13/62 SPUD. 6/7/62 COMP. 9/4/62 of NW/4CONT. Wakefield Drlg. Tools* /GEOL.

NAME PRODUCING INTERVAL	COMPLETION RECORD FROM - TO	PERF. W/HOLES	TREATMENT RECORD
<u>Red Cave</u>	<u>1210-32</u>	<u>28</u>	<u>500 A Frac</u>
b			
c			
d			



I. P. OIL/DIST.	WTR.	GAS	M.C.F.P.D.	CHK.	HRS.
		<u>4420</u>			<u>24</u>
b					
c					
d					

D & A ()

SIP# _____ FI TP # _____ FI CPH _____ SIBHP _____

GOR. _____ GR. _____ PBTD 1240 TD 2100

SIZE	DEPTH	CASING W/SAX.	CEMENT RECORD SIZE	DEPTH	W/SAX.
<u>8"</u>	<u>@ 1190</u>	<u>550</u>			
<u>4½"</u>	<u>@ 1350</u>	<u>75</u>			

OPERATOR Anadarko Prod. Co. WELL NO. 1 Interstate "F" ELEV. 3502 Gr

SAMPLE TOPS	DEPTH	SUB SEA	ELEC. TOPS (Twin)	DEPTH	SUB SEA
<u>*Rig #7</u>			<u>Gr Tops & Datums:</u>		
<u>B/Cimm</u>	<u>1195</u>	<u>+2307</u>	<u>Red Cave</u>	<u>1198</u>	<u>+2304</u>
<u>RTD (Red Cave)</u>	<u>2100</u>	<u>+1402</u>	<u>LTD</u>	<u>N.A.</u>	
<u>Ø #1 (Red Cave)</u>	<u>1195-1236:</u>	<u>R 23'</u>	<u>siltstone, 6'</u>	<u>gray sh,</u>	
			<u>12'</u>	<u>red sh.</u>	
<u>Ø #2 (Red Cave)</u>	<u>1236-86:</u>	<u>R 22½'</u>	<u>Red sh, 17½'</u>	<u>silts, lots</u>	
			<u>10'.</u>		
<u>Ø #3 (Red Cave)</u>	<u>1286-1336:</u>	<u>R 50' = 23'</u>	<u>silts, 27'</u>	<u>Red sh.</u>	
<u>Ø #4 (Red Cave)</u>	<u>1336-86:</u>	<u>R 20.7</u>	<u>silts, 29.3</u>	<u>Red sh.</u>	
<u>RTD 2100, Log, WLT #1 (RC)</u>	<u>1540½:</u>	<u>Op 70",</u>	<u>R 5100 cc wtr,</u>		
		<u>58% SW,</u>	<u>IBHP 490#/20",</u>	<u>FBHP 480#/10".</u>	
<u>WLT #2 (RC)</u>	<u>1266-68½:</u>	<u>Op 60",</u>	<u>R 15,000 cc filt wtr (8%</u>		
		<u>SW) IBHP 380#/5",</u>	<u>FBHP 380#/5".</u>		
<u>WLT #3 (RC)</u>	<u>1229-31½:</u>	<u>Op 60",</u>	<u>R .1 cfg + 1060 cc filt wtr,</u>		
		<u>IBHP 0#,</u>	<u>FBHP 260#/41".</u>		
<u>4½" @ 1350'</u>	<u>w/75 sx,</u>	<u>CO 1316,</u>	<u>Perf 10/1277-82 (RC)</u>	<u>Swb 56</u>	
	<u>GWP/8 hrs,</u>	<u>Clor 83,000 PPM,</u>	<u>PB 1240 PBTD,</u>	<u>Perf 8/1228-32</u>	
	<u>(RC) 500 A,</u>	<u>6 HBD,</u>	<u>600 Mcfgpd,</u>	<u>Perf 20/1210-20 (RC)</u>	<u>5 HBD,</u>

800 MCF, frac/15,000 gal jell wtr x 15,000 sd, 4 hr BD g
9,240 MCF (wtr wet) 70 hr SIP 360, 4 hr BD g 6,528 MCF
mist of XW, 4 pt cal of g 4,420 MCF, SIP 334, red
Cave 1210-32, 8/28/62.

LIBERAL ELECTRIC LOG TOPS

3502 GL

B. C. A. 1198 (+2304) IP OF = 4,420 MCF
Winfield 1928 (+1574)
RTD 2100'