


THE CARTER OIL CO.
W.H.Seibert No. 1.

4-34-8W

SEC. 4 T. 34 R. 8W
C SW NW
660' fr S & W Lines

Total Depth. 5220' P.B. 4628 P.B. 4500
Comm. 3-6-37 Comp. 5-26-37
Shot or Treated. 2000 Gals.
Contractor. Helmerick-Payne
Issued. 7-3-37 Rotary O-5220'

County. Harper



CASING:
15 1/2" 293'
6 5/8" 4680'

JUL 3 1937

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

red rock, shale	350	lime	4807
red rock	600	cored lime	4810
shale	1026	lime	4918
shale, sand	1286	cored lime	4921
lime, shale streaks	1380	shale	4970
brkn lime	1520	cored lime	5062
lime, shale	1670	sand, lime	5075
lime	1735	lime hrd	5083
shale	1810	lime	5094
lime	1824	sand, lime	5100
shale, lime shells	1850	sdv lime hrd	5106
lime, shale streaks	1875	sand hrd	5112
shale	1890	sand, lime	5118
lime	1940	lime	5130
shale	1970	lime, shale	5180
lime	2018	cored shale	5190
lime, shale streaks	2041	cored sand	5202
lime	2203	reamed	5203
shale	2303	cored lime	5220
lime, shale streaks	2363	Total Depth.	
shale	2405	<u>TOPS</u>	
lime	2457	Simpson	5034
shale	2555	Viola	4983
shale, lime streaks	2630	Wilcox	5034
brkn lime, shale	2765	Miss	4628-4918
lime	3025	Kansas City	4035
shale	3145	Siliceous	5202
brkn lime, shale	3215		
lime	3347		
brkn lime, shale	3450		
shale	3522	Shot 2000 Gals. 4592-5220	
brkn lime	3546	Shot with 20 Qts. 4596-4610	
shale	3890		
lime	3940	Well plugged to top 6-8-37	
shale	4057		
lime	4341		
shale	4397		
lime	4413		
shale, lime streaks	4434		
shale	4440		
brkn lime, shale	4462		
lime	4485		
brkn lime, shale	4513		
lime	4525		
shale	4578		
lime, shale	4615		
		lime	4630
		cored lime	4635
		lime	4650
		cored lime	4680
		lime	4760
		lime hrd	4762
		lime	4776
		lime, shale	4783