

Company-SINCLAIR OIL & GAS CO.
Farm-L. T. Helmly No. 1

SEC. 3 T. 35 R. 10W
SW SW SE

3-35-10W

Total Depth. 5488
Comm. 1-19-55 Comp. 3-11-55
Shot or Treated.
Contractor. Adkins Drilling Co., Inc.
Issued. 1-7-56

County Barber
KANSAS



CASING:
10 3/4 231' w/ 200 sx cmt.

Elevation. 1286

Production. Dry

Figures indicate Bottom of Formations.

red bed & sand	180
shale	235
plug & cement	235
red bed & shells	800
shale & shells	1050
shale & lime shells	1510
shale & shells	1600
shale & lime	1915
Ft. Riley lime	2040
shale & lime	2285
shale	2371
lime & shale	2495
shale & shells	2780
lime & shale	3726
shale	3835
shale & lime streaks	3920
shale & sand	4052
shale & lime	4272
lime & chert	4398
lime	4715
cored: rec. 52'	4767
cored: rec. 38'	4806
shale & sand	4849
cherty lime	4907
lime & chert	4932
lime	4939
lime & chert	4948
shale & lime	5148
cored: rec. 24'	5172
lime & shale	5185
lime	5195
lime & chert	5201
lime & shale	5253
lime & sand	5275
sand, lime & shale	5301
lime & sand	5350
lime & shale	5391
sand & shale	5431
sand & lime	5479
Arbuckle lime	5488
Total Depth	

SCOUT TOPS:	
Heebner	3611
Kansas City	4200
Mississippi	4710
Maquoketa	5083
Viola	5149
Simpson	5236
Arbuckle	5457