2-35-32W


WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company- J. M. HUBER CORPORATION
Farm- Light "C" No. 1

SEC. 2 T. 35 R. 32W
CSW SW

Total Depth. 6314 SJTD 6327
Comm. 3-22-53 Comp. 5-14-53
Shot or Treated.
Contractor.
Issued. 6-20-53

County Seward
KANSAS



Elevation. 2757

Production. 156 BOPD,
21,687,000 Gas

CASING:
13 3/8 624' cemented
9 5/8 2400' cemented
5 1/2 6040' cemented

Figures Indicate Bottom of Formations.

sand 1100 to	1400
sand & shale	1950
shale & anhydrite	2060
anhydrite	2570
dolomite	2850
lime	3850
shale & lime	3970
sandy lime & shale	4140
shale & lime	4430
lime	5530
lime & shaley lime	5700
lime	5790
lime & shale	5920
shale	5967
sand (oil & gas)	5980
shale & limey shale	6185
lime	6314
Total Depth	

Total Depth by Schlumberger 6327

TOPS:

Hollenberg	2570
Herrington	2625
Krider	2676
Winfield	2748
Ft. Riley	2808
Lansing	4429
Marmaton	5388
Morrow	5917
Chester(Mississippi)	6192

DST #1: 5970-90, open 22 min. gas to surface in 2 min., oil in 7 min. gauge 7.5 to 8.0 MM gas in 20 min. rec. 180' oil. FP 1590# SI 25 min. BHP 1785#