

90313 X

MAP NO. \_\_\_\_\_ ELEV. 3518 KB 3515 DF

STATE Kansas COUNTY Morton SEC. 6 Twp 35 S Rge 41 W

OPERATOR Cities Service Oil Company LOC. C SW NE

WELL NO. 1 FARM NAME Fulkerson "B" FT. FROM \_\_\_\_\_ LINE \_\_\_\_\_

POOL Wilburton Ext. FT. FROM \_\_\_\_\_ LINE \_\_\_\_\_

FR. 9-7-60 SPUD 9-5-60 COMP. 11-18-60

CONT./GEOL. Holm Drilling Tools Shell Int.

NAME PRODUCING INTERVAL FROM - TO PERF. W/HOLES TREATMENT RECORD

a. Topeka 3096-3261 232 19,000 A

b. \_\_\_\_\_ \_\_\_\_\_ \_\_\_\_\_ 40 Ball sealers

c. \_\_\_\_\_ \_\_\_\_\_ \_\_\_\_\_ \_\_\_\_\_

d. \_\_\_\_\_ \_\_\_\_\_ \_\_\_\_\_ \_\_\_\_\_

a I. P. OIL/DIST. \_\_\_\_\_ WTR. COF GAS 2100 M.C.F.P.D. \_\_\_\_\_ CHK. \_\_\_\_\_ HRS. \_\_\_\_\_

b " " " 21,000 " " " " " "

c " " " " " " " " " "

d \_\_\_\_\_ \_\_\_\_\_ \_\_\_\_\_ \_\_\_\_\_


D & A ( )

SIP# 395.4 FI TP # \_\_\_\_\_ FI CP# \_\_\_\_\_ SIBHP \_\_\_\_\_

GOR. \_\_\_\_\_ GR. \_\_\_\_\_ PBTD 3288 TD 5390

SIZE DEPTH CASING - CEMENT RECORD SIZE DEPTH W/SAX.

8-5/8" 1482 650

4 1/2" 3454 250

OPERATOR Cities Service Oil WELL NO. 1 Fulkerson "B" ELEV. 3515 DF

SAMPLE TOPS	DEPTH	SUB SEA	ELEC. TOPS	DEPTH	SUB SEA
			Topeka	3096	
			Heebner	3458	
			Toronto	3480	
			Lansing	3612	
			Marmaton	3854	
			Cherokee	4359	
			Morrow	4688	
			Morrow Sd	4776-90	
			Morrow Sd	5098-5118	
			Morrow Sd	5123-48	
			Keyes	5183	
			Chester	5218	
			Ste. Genevieve	5370	

DST # 1 (Topeka) 3083-3155 op 60", GTS 3", Ga 499 Mcf/15", Ga 1860 Mcfg/60", Rec 300 GCM, IFP 180#, FFP 225#, SIP430/20"

DST # 2 (Morrow) 4777-99 op 60", Rec 2280 GIP + 100' gas & salty watery mud + 850' SW, IFP 0#, FFP 420#, SIP 1390#/20".

DST # 3 (Morrow) 5050-70 op 30", Bypass tool - rec 2' M, IFP 0#, FFP 0#, SIP 0#/15".

DST #4 (Keyes) 5102-40, op 30 min, rec 15' Mud, FP 25-25,  
SIP 820/15:

TD 5390, ran Elog, 4½" @ 3454/250 sx.

RUCT.

P/Topeka/32/3408-16 NS, 1500 A, Swb 200 GSWPH/NT, Sq Pf w/150  
sx, PB 3405.

P/Topeka/32/3370-78, 3000 A, Swb 500 GSWPH/NT. BP 3399.

P/Topeka/24/3255-61, 1000 A, g 1,790 MCF + 40 GWPH/9 hr. 3000 A  
g 991 MCF + 20 GWPH/18 hrs.

P/Topeka/32/3246-50, 20/3231-36, 3000 A + 40 ball sealers, g  
12 MCF + wtr, g 1,100 MCF/30".

P/Topeka/56/3172-86, 12/3158-60, 20/3148-53, 12/3141-44, 32/  
3130-38, 24/3096-3102, BP @ 3220, g 1,140 MCF, 7000 A,  
Flwd load, g 8,860 MCF/6 hrs, g 8,460 MCF/20 hrs, 15,000  
A, rec load, pulled plug @ 3220, PB 3288.

COF = 21,000 MCF, SIP 395.4#.

COMPLETE.

LIBERAL TOPS

3518 KB

Topeka 3096 (+422)

Heebner 3458 (+60)

Toronto 3480 (+38)

Lansing 3612 (-94)

Marmaton 3864 (-346)

Cherokee 4359 (-841)

Morrow 4688 (-1170)

"L" Sand 4776 (-1258) 4/14

"S3" Sand 5098 (-1580) 6/20

"S3" Sand 5123 (-1605) 9/25

Keyes 5183 (-1665) 15/35

Chester 5218 (-1700)

St. Gen 5370 (-1852)

4365  
3556  
809