

11-148W MAP NO. 82

SEC. 5-35S-41W

STATE Kansas COUNTY Morton

LOC. C SE SE

OPER. Cities Service Oil Co., Guymon, Okla.

FT/FR _____ LINE

WELL #1 FARM Hoopingarner "D"

L-53505

FT/FR _____ LINE

LOC. Wilburton Ext.

ELEV. 3498

GR. 3506

DF 3508 KB

CONT. Holm Drilling

GEOL. Vernon Howell

CO. _____

F.R. 9-26-63 SPUD 9-24-63

COMP. 11-12-63


TD. 5130 FM. Morrow

PBTD. _____

Morrow "G" 5116 -24 32 500A & Frac.

State Pot: P 180 BOPD-NW, Gray 45 deg.

8-5/8" @1501' w/650 Sx. 5 1/2" @5129' w/150 Sx.



Data Inc.

COMP
RECORD

KB Log Tops:

Top	3106	+ 402	Mrw	4724	-1216
Shaw "A"	3240	+ 268	Mrw sd	5100	-1592
Shaw "B"	3268	+ 240	53 B/sd	5122	-1614
Hb	3490	+ 18	LTD	5130	-1622 (msd)
Tor	3509	- 1			
Lan	3642	- 134			
Marm	3908	- 400			

DST #1 (Mrw "G") 5080-5130, Op 1 hr, GTS/15', Ga 49,000 cfg/20'.
TSTM/30', Rec. 1000' oil, NW, No ISIP, FP 88#, FFP 792#, FSIP
1150#/30'. RTD 5130' (Mrw) E. Log, 5 1/2" @5129' w/150 Sx. CO. 5125'
32/5116-24 (Mrw sd) § 2 1/2 BO 5 hrs, 500A, § 1d, § 6BO, NW, 4 hrs. sd-
oil, frac. 10,000 oil x 5000# sd., Rec. 1d, § 306 BO-NW/24 hrs.
(45°) GOR-TSTM, POP, State Pot. (8 hr pump rate) Cal P. 180
BOPD-NW, Gr. 45 deg. Morr "G" 5116-24 - COMPLETED 11-5-63