90338

9-251 W

MAP NO. 82 SEC. 10 TWP. 35S RGE. 42W

STATE Kans COUNTY Morton App LOC. C NE SE

OPERATOR Anadarko Prod. Co. 677 FT. FROM E LINE

[redacted] NO. 1-A FARM NAME Barnes "B" 1951 FT. FROM S LINE

[redacted] Taloga ELEV. 3577 GR 3587 DF 3589 KB

FR. 2/28/62 SPUD 2/28/62 COMP. 9/18/62

CONT. Garvey Drlg. Co. /GEOL.

COMPLETION RECORD

	NAME PRODUCING INTERVAL	FROM — TO	PERF. W/HOLES	TREATMENT RECORD
a	Morrow	4617-22	20	500 A & Frac
b				
c				
d	Cal Pump:			

a I. P. OIL/DIST. 200 BO WTR. NW GAS M.C.F.P.D. CHK. HRS. 24

b " " " " " "

c " " " " " "

d

D & A ( )

SIP# FI TP # FI CP# SIBHP

GOR. GR. PBTD 4636 TD 4650

CASING - CEMENT RECORD

SIZE	DEPTH	W/SAX.	SIZE	DEPTH	W/SAX.
8 5/8"	@ 1432	700			
4½"	4647	100			

OPERATOR Anadarko Prod. Co. WELL NO. 1-A Barnes "B" ELEV. 3577 GR

SAMPLE TOPS	DEPTH	SUB SEA	ELEC. TOPS	DEPTH	SUB SEA
RTD (Morr)	4650	-1073			

NOTE: Skid rig 34" from #1 Barnes "B" (New loc = 677' FEL & 1951 FSL of Sec. 10) (4700' Tst)

GR Tops & Datums

Waub	2720	+ 857
Top	2925	+ 652
Grnwood Lans.	3174	+ 403
Lans	3367	+ 210
Marm	3852	- 275
Chero	4012	- 435
Morr Form	4240	- 663
Morr Lm	4283-92	- 706
Morr Lm	4296-4300	- 719
Morr Sd	4480-98	- 903
Morr Sd	4614-24	-1037
LTD	N.A.	

RTD 4650, Logged.

WLT #1 (Morr) 4488, Op 75", R 20,250 cc wtr(38% form wtr), SP 1375#, FBHP 1500#/15".

WLT #2 (Top) 3058-60½, Op 1 hr., R 2700' filt wtr, FBHP 460#/21",.

[redacted]LT #3 (Top) 3033-35½, Op 1 hr., R 3500' cc wtr, FBHP 400#/17".

4½" @ 4647 w/100 sx, CO 4636 PBTD.

20/4617-22 (Morr) Swb 8½ BO & tr form wtr, 2½ hrs, 500 A, Swb 1d, Swb 9 BO/5 hrs, Frac (10,000 GO, x 10,000# sd) Rec 1d, Fl 79 BO/3 hrs., kill well, w/120 BO 2-3/8" tbg 4630, Rec all 1d, Swb 96 BNO/7 hrs. Cal Pump 200 BOPD, Morr 4617-22, 9/1/62.

COMPLETED

LIBERAL ELECTRIC LOG TOPS

3577 GL

Wabaunsee 2718 (+859)
Topeka 2924 (+653)
Toronto 3274 (+303)
Lansing 3364 (+211)
Marmaton 3760 (-183)
Morrow 4242 (-665)
"S-2" 4478 (-901) 18/20; WLT 20,250 cc wtr
"S-3" 4612 (-1035) 8/10; ¢ 200 BOPD
TD 4650