

KANSAS GEOLOGICAL SOCIETY
KANSAS WELL LOG BUREAU - KANSAS WELL SAMPLE BUREAU
KANSAS GEOLOGICAL SOCIETY BUILDING
508 EAST MURDOCK - WICHITA, KANSAS

34-3-27W

COMPANY **RAYMOND OIL, INC.**

SEC. 34 T. 3 R. 27W
 LOC. NE NW NW

FARM **Steffen**

NO. 1

TOTAL DEPTH **4047**

COMM. **9-27-66**

COMP. **10-9-66**

SHOT OR TREATED

CONTRACTOR **Abercrombie Drlg.**

ISSUED **2-25-67**

COUNTY **Decatur**

KANSAS

CASING

20	10	
15	7" @ 290.90'	w/150 sx
12	6	
13	4 1/2" @ 3804'	w/125 sx

ELEVATION **2619'KB**

PRODUCTION **ST TST: PMP**
139 BOPD, NW (LANS 3530-3630)
GR 35.6

FIGURES INDICATE BOTTOM OF FORMATIONS

0	75	Shale & Sand-Clay
75	298	Clay & Sand Stringers
298	800	Shale
800	1375	Shale & Shells
1375	1985	Shale & Sand
1985	2142	Shale
2142	2180	Anhydrite
2180	2208	Shale
2208	2335	Shale & Shells
2335	2950	Shale & Lime
2950	3505	Lime & Shale
3505	3565	Lime
3565	3585	Lime & Shale
3585	3620	Lime
3620	3725	Lime & Shale
3725	3728	Lime
3728	3900	Shale & Lime
3900	4040	Lime
	4040	Rotary Total Depth

Set 7", 24# pipe at 290.90 with 150 sacks of HA-5 cement.

Set 4-1/2", 9-1/2# casing at 3804' with 125 sacks of posmix cement

TOPS: SCOUT

ELEVATION: 2619 K.B.

Anhydrite	2144
Heebner	3480
Lansing	3522
Base Kansas City	3730
Arbuckle	3905