

KANSAS GEOLOGICAL SOCIETY
 KANSAS WELL LOG BUREAU - KANSAS WELL SAMPLE BUREAU
 KANSAS GEOLOGICAL SOCIETY BUILDING
 608 EAST MURDOCK - WICHITA, KANSAS

16-3-28W


COMPANY HALLIBURTON OIL PROD.

SEC. 16 T. 3 R. 28W
 LOC. C SE SW

FARM Bremer

NO. 1

COUNTY Decatur
 KANSAS



TOTAL DEPTH 3930

COMM. 9-8-66

COMP. 9-15-66

SHOT OR TREATED

CONTRACTOR Abercrombie Drlg.

ISSUED 12-10-66

CASING

20	10	
15	7"	@ 264' w/125 SX
6		
5		

ELEVATION 2725' KB

PRODUCTION DRY (Lans)

FIGURES INDICATE BOTTOM OF FORMATIONS

0	275	Shale & Sand Stringers	
275	1875	Shale	
1875	2139	Shale & Sand	TOPS: SCOUT
2139	2411	Shale	Anhydrite 2411-43
2411	2444	Anhydrite	Heebner 3698
2444	2685	Shale	Lansing 3742
2685	2960	Shale & Shells	
2960	3250	Shale & Lime	
3250	3450	Lime & Shale	
3450	3565	Lime	
3565	3845	Lime & Shale	
3845	3930	Shale & Lime	
	3930	Rotary Total Depth	

Set 7" surface casing at 264 feet with 125 sacks of HA-5 cement.

Dry and Abandoned

ELEVATION:

2725 K.B.
 2724 D.F.
 2718 G.L.

OF KANSAS)
) SS
 EDGWICK)