

State Geological Survey
WICHITA, BRANCH

28-3-284

KANSAS DRILLERS LOG


S. 28 T. 3 R. 28 ^E/_W

Loc. NE NE NW 5/2 NW NW

API No. 15 — 039 — 20,346
County Number

County Decatur

640 Acres
N



Locate well correctly

Elev.: Gr. 2741'

DF 2744' KB 2746'

Operator Raymond Oil Company, Inc.	
Address 200 West Douglas, Suite 800, Wichita, Kansas 67202	
Well No. #1	Lease Name Pachner
Footage Location 990 feet from (N) (X) line 660 feet from (E)(W) line	
Principal Contractor Rains & Williamson	Geologist Chas. B. Spradlin
Spud Date 8-11-76	Total Depth RTD 3958
Date Completed 8-20-76	P.B.T.D.
Oil Purchaser	

CASING RECORD

Report of all strings set — surface, intermediate, production, etc.

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
Surface	12-1/4"	8-5/8"		293	50/50 Pos	200	2% gel, 3% cc

LINER RECORD

PERFORATION RECORD

Top, ft.	Bottom, ft.	Sacks cement	Shots per ft.	Size & type	Depth interval

TUBING RECORD

Size	Setting depth	Packer set at

ACID, FRACTURE, SHOT, CEMENT SQUEEZE RECORD

Amount and kind of material used	Depth interval treated

INITIAL PRODUCTION

Date of first production		Producing method (flowing, pumping, gas lift, etc.)			
RATE OF PRODUCTION PER 24 HOURS	Oil	Gas	Water	Gas-oil ratio	CFPB
	bbls.	MCF	bbls.		
Disposition of gas (vented, used on lease or sold)			Producing interval (s)		

INSTRUCTIONS: As provided in KCC Rule 82-2-125, within 90 days after completion of a well, one completed copy of this log shall be filed with the State Geological Survey.

1	Pachner	Dry Hole	
S <u>28</u> T <u>3</u> S <u>R</u> <u>28</u> ^{5x} _W			
WELL LOG		SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION.	
Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.			
FORMATION DESCRIPTION, CONTENTS, ETC.	TOP	BOTTOM	NAME
			DEPTH
DST No. 1 30/45/45/60 Rec. 1269' mdy wtr FP 114-321, ISIP 1339, FP 344-617, FSIP 1271	3675	3729	LOG TOPS
			2419
			2452
			3498
			3540
DST No. 2 30-30-30-30 Rec. 2' free oil - 3' OCM FP 45-45, ISIP 572, FP 45-45, FSIP 114	3731-	3760	Heebner
			3706
			3737
			3750
			3946
			3962
DST No. 3 30-30-30-30 Rec. 5' mud - no sho FP 45-45, ISIP 229, FP 45-45, FSIP 137	3762	3815	
DST No. 4 MIS-RUN	3815	3850	
DST No. 5 45-45-45-45 Rec. 600' mud FP 137-160, ISIP 1791, FP 229-366, FSIP 1769	3800	3850	
DST No. 6 30-45-45-60 Rec. 360' mdy wtr FP 206-206, ISIP 1791, FP 206-229, FSIP 1746	3761	3850	
D & A - Plugged 8-20-76			
USE ADDITIONAL SHEETS, IF NECESSARY, TO COMPLETE WELL RECORD.			
Date Received	RAYMOND OIL COMPANY, INC.		
	 Wm. M. Raymond ^{Signature} President		
	Title		
	August 25, 1976		
	Date		

2-3-251938