

Plotted Job.

13-4-23W

CITIES SERVICE OIL CO.
Boucher No. 1.

SEC.13 T. 4 R. 23W
NEc NE
330'S 330'W NE Cor.

Total Depth. 3813'
Comm. 8-4-41 Comp. 8-22-41
Shot or Treated.
Contractor. Twin Drlg.Co.
Issued. 10-11-41

County. Norton



CASING:
8 5/8" 325' Cem.

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

surface	60
surface sand	190
shale	200
shale & shells	325
shale & lime shells	500
sdv lime & shale brks	620
sdv shale & shells	700
shale dk & shells	1130
sdv shale dk	1256
sdv shale	1310
sand & iron hrd	1427 ✓
shale & shells	1795
shale dk & shells	1850
shale red & shells	1905
anhydrite	1937
shale & shells	1950
lime lgt med	1980
shale & lime shells	2300
lime & shale brks	2330
shale & lime shells	2375
shale red & shells sft	2410
shale red sft	2475
lime & shale brks	2732
lime gy hd & shale brks	2807
lime & shale brks	2826
lime gy hrd	2850
lime lgt hrd	2920
lime gy hrd	3102
lime gy hrd & shale brks	3165
lime gy hrd	3274
lime med gy	3345
lime med	3386
lime hrd	3543
ohert hrd	3576
lime & shale	3582
lime hrd	3639
lime & shale hd bkn	3683
lime hrd	3692
lime & shale	3696
lime & shale brks	3710
lime & shale med	3728
lime & shale	3740
granite wash	3813
Total Depth.	

Tops: Lansing 3439
Granite wash 3724
Granite 3810
Penetration 3