

WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas


14-5-20W

Company- CITIES SERVICE OIL CO.
Farm- Templeton No. 8

SEC. 14 T. 5 R. 20W
SW SW NE
330' N & 330' E of Cent.

Total Depth. RTD 3542 = 3542 SLM
Comm. 11-2-52 Comp. 11-11-52
Shot or Treated. Acid 1000 gals 11-20-52
Contractor. R. W. Rine Drilling Co.
Issued. 1-17-53

County Phillips
KANSAS



CASING:
8 5/8 202 w/ 200 sx cement
5 1/2 3537 w/ 150 sx cement

Elevation. 2150

Production. Pot. 36 BO, no wtr.
24 hrs.

Figures Indicate Bottom of Formations.

surface clay & sand	202
shale, shells & chalk	630
shale & shells	1630
anhydrite	1670
shale & shells	2300
lime & shale	3294
lime	3538
cored: dolomite rec. 3'1"	3542
Total Depth	3542 RTD = 3542 SLM

TOPS	
Heebner	3222
Dodge	3245
Lansing	3265
Arbuckle	3535
Penetration	7

84' oil in 1 hr.
717' oil in 18 hrs.