WELL LOG BUREAU -- KANSAS GEOLOGICAL SOCIETY
412 Union National Bk. Bldg., Wichita, Kansas


23-5-20W

Company. CITIES SERVICE OIL CO.
Farm. Hansen "C" No. 4

SEC. 23 T. 5 R. 20W
CN/2 NE NW
330' S & 660' W of N/4c

Total Depth. 3569' PBTD 3527'
Comm. 8-28-46 Comp. 9-6-46
Shot or Treated. Acid 1000 gals. 3329-40 9-13-46;1000 g. 3306-14
Contractor. R. W. Rine Drilling Co.
Issued. 1-11-47

County. Phillips
KANSAS



Elevation. 2163 KB

CASING:
8-5/8" 197' Cem
5-1/2" 3564' Cem

Production. Phy. Pot: 411 oil, no wtr, 24 hrs.

Figures Indicate Bottom of Formations.

surface	0-40
clay & sand	197
shale & shells	530
shale & sand	1320
shale & shells	1640
lime	1685
shale & shells	2415
shale & lime	2670
lime & shale	2680
lime	2785
shale & lime	3287
lime	3464
shale	3490
shale & sdy lime	3525
cored Cong.(rec.4')	3530
conglomerate	3560
lime	3564
cored lime (rec.5')	3569
Total Depth	

Schlumberger

Tops:

Lansing	3262
Arbuckle	3562
Penetration	7

Drilled cement to 3527 SLM

Perf. 12 shots 3345-56
1½ bailers mud and wtr in 1 hr.
Perf. 36 shots 3329-40.
Set Halliburton plug @ 3341.
Perf. 24 shots 3306-14.