


WELL LOG BUREAU--KANSAS GEOLOGICAL SOCIETY
412 Union National Bk. Bldg., Wichita, Kansas

23-5-Jan

Company - CITIES SERVICE OIL CO.
Farm - Hansen "C" No. 6

SEC. 23 T. 5 R. 20W
CN/2 SE NW
990' N & 660' W of Cen

County. Phillips
KANSAS



Total Depth. 3524' PBTD 3493'
Comm. 10-4-46 Comp. 10-12-46
Shot or Treated. Acid 2000 gals. 10-19-46
Contractor. R. W. Rine Drilling Co.
Issued. 1-11-47

CASING:

8-5/8" 203' Cem
5-1/2" 3517' Cem

Elevation. 2173' *h*

Production. Phy. Pot: 490 psi,
0.8% B.S., 24 hrs.

Figures indicate Bottom of Formations.

surface	0-40
sand	70
shale & shells	204
shale, shells & sand	900
sand & shale	1570
shale & lime	1640
lime	1685
shale & shells	2385
shale & lime	2498
lime	2530
lime & shale	2738
lime	2764
shale & lime	2785
shale & shells	2985
lime	2995
lime & shale	3260
lime	3395
shale & lime	3440
lime	3512
shale	3516
lime	3518
cored lime (rec. 6)	3524
Total Depth	

Schlumberger

Tops:
Lansing 3253
Arbuckle 3515
Penetration 9

Drilled cement to 3493 SIM
Perf. 48 shots 3321-34
550' fluid in 2 hrs.
2500' oil in 17 hrs.