

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY  
412 Union National Bank Bldg, Wichita, Kansas.

Plotted gwr  
28-5-20w

CITIES SERVICE OIL CO.  
Vehige No. 2

SEC. 28 T. 5 R. 20 W.  
NE SW SW  
990' North 990' East SW cor.

Total Depth. 3595  
Comm. 7-14-41 Comp. 7-26-41  
Shot or Treated. 1000 Gal. 7-27-41  
Contractor. R.W. Rine Drilling Co.  
Issued. 1-10-42

County Phillips



CASING.

85/8" 150' Cem.  
5 1/2" 3584' Cem.

Elevation.  
Echometer  
Production. Pot. 1332 B.  
1668 wtr 24 hrs.  
(Ind. Cap. 15,284 bbls)

Figures Indicate Bottom of Formations.

|                                 |      |
|---------------------------------|------|
| sand and shale                  | 25   |
| shale and shells                | 1270 |
| sand                            | 1400 |
| shale and shells                | 1730 |
| anhydrite and lime              | 1750 |
| shale and shells                | 2135 |
| lime and shale                  | 2380 |
| shale and sand                  | 2535 |
| sdv lime                        | 2595 |
| lime and shale                  | 2660 |
| shale and shells                | 2885 |
| lime and shale                  | 3230 |
| lime                            | 3296 |
| lime and shale                  | 3330 |
| lime                            | 3502 |
| lime hard                       | 3541 |
| lime soft                       | 3560 |
| lime hard                       | 3573 |
| lime                            | 3585 |
| 3585 Rot. T. D. Equals 3585 SLM |      |
| dolomite                        | 3595 |

Total Depth.

Top of Arbuckle 3583  
Penetration 12'

FILLUP.

500' in 1 hour.  
600' in 1 1/4 hours  
1550' in 3 hours.  
1950' in 4 hours.  
2600' in 12 hours.