

KANSAS WELL LOG BUREAU --- KANSAS GEOLOGICAL SOCIETY

508 EAST MURDOCK - WICHITA, KANSAS

30-5-20W

COMPANY CITIES SERVICE OIL CO.

SEC. 30 T. 5 R. 20W

FARM States "B" NO. 7

LOC. NE SW NW
990' E, 990' N of W $\frac{1}{4}$ corner

COUNTY Phillips


TOTAL DEPTH 3654 PB 3651

COUNTY

COMM. 10-4-50 COMP. 10-23-50

KANSAS

SHOT OR TREATED



CONTRACTOR R. W. Rine Drlg. Co.

ISSUED 12-30-50

CASING

8 5/8" 198' cem w/250 sx.
5 1/2" 3648' cem w/150 sx.

ELEVATION 2211

PRODUCTION Phys. 290 oil,
5% water.

FIGURES INDICATE BOTTOM OF FORMATIONS

clay, sand	100
sand	135
shale, shells	198
shale	650
sand, shale, shells	875
sand	950
shale, shells	1100
sand, shells	1500
shale, shells	1685
redbed, shale	1750
anhyd.	1790
shale	2085
shale, shells	2190
lime, shale	2285
shale, shells	2535
lime, shale	2865
shale	2985
shale, lime brkn	3105
lime, shale	3340
lime	3390
lime cherty	3440
lime, chert	3485
lime	3630
lime, shale	3636
lime	3642
cored: dolo, shale	
rec. 2 1/2'	3647
cored: sand, rec. 4 1/2'	
3652 RTD = 3652 SLM	3652
sand	3654
Total depth PB 3651	

Tops:

Lansing	3405
Arbuckle	3636
Reagan	3647
Penetration	7'

Fillup:
1300' fluid in 45 mins.
1900' fluid in 1 1/2 hrs.
2280' fluid in 2 3/4 hrs.
2370' fluid in 3 3/4 hrs.
2430' fluid in 4 3/4 hrs.
2475' fluid (1255' oil and 1220' water) in 8 3/4 hrs.
Plugged back 3654-3651 w/plastic.
10-27-50, pumped 224 oil, 68 water
24 hrs..