
WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
412 Union National Bk Bldg., Wichita, Kansas

CITIES SERVICE OIL CO.
Johnson "B" No. 2.

SEC.32 T.5 R.20W
NE NW SW
330'S 996'E of W¼ Cor.

Total Depth. 3636 =3633 SLM
Comm. 5-25-41 Comp. 6-8-41
Shot or Treated. 2000 Gals.6-22-41
Contractor. Harbar Drlg.Co.
Issued. 7-19-41

County. Phillips



CASING:
10¾" 175' Cem.
5½" 3633' Cem.

Elevation.

Production. Echo,Pot.472OB.
No wtr

Figures Indicate Bottom of Formations.

cellar	0 - 8
sand	60
clay & sand	169
shale & shells	180
gravel	210
shale & shells	490
shale	975
shale & shells	1240
shale & sand	1460
shale & shells	1735
anhydrite	1770
shale & sand shells	1955
shale & shells	2425
lime	2465
shale & lime shells	2530
shale & shells	2585
shale & lime shells	2670
shale & lime	2800
lime	2810
shale & lime	3105
lime	3175
shale & lime	3230
lime	3562
shale & lime	3575
shale	3604
cored hrd sand(rec5')	3615
cored sand(rec 1½')	3625
cored schist(rec.4')	3630
cored schist & granite (rec 5½')	3636

3636 Rot.TD =3633 SLM
Total Depth.

Tops:

Reagan(Corr.)	3600
Schist	3622
Granite	3632
Penetration	1

Drilled cement to 3631 SLM

6-20-41 perforated by
Lane-Wells as follows:
11 shots 3598-3609
450' fluid in 20 min.
24 shots 3600-3608
1000' fluid in 40 min.
59 shots 3608-22
1650' fluid in 1 hr
2200' fluid in 2 hrs
2730' fluid in 4 hrs