

WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY.
412 Union National Bank Bldg, Wichita, Kansas.


32-5-20W

CITIES SERVICE OIL CO.
Johnson "B" No. 7

SEC. 32 T. 5 R. 20 W.
NE SE SW
990' N and 330' W of S $\frac{1}{4}$ cor.

Total Depth. 3577
Comm. 5-12-42 Comp. 5-24-42
Shot or Treated. None
Contractor. R.W. Rine Drilling Co.
Issued. 7-4-42

County. Phillips



CASING.

85/8" 161' cemented.
5 $\frac{1}{2}$ " 3566' cemented.

Elevation. 2175

Production. Pot. 903 B.
63BW, Echo.

Figures Indicate Bottom of Formations.

surface sand & shale	161
shale	350
shale shells and sand	1090
shale and sand	1615
shale	1690
anhydrite	1720
shale and shells	2000
shale and lime	2140
shale and shells	2580
lime and shale	2623
shale and shells	2745
shale and lime	2935
shale and shells	3046
shale and lime	3318
lime	3570
cored sand (Rec. 4')	3574
3574 Rot T.D. = 3573 SLM	
sand	3577
Total Depth.	

Corr. Top Reagan 3566
Penetration 11'

Pillup.

600' oil in 30 Min.
1200' oil in 1 $\frac{1}{2}$ hours.
2000' oil in 3 $\frac{1}{2}$ hours.
2200' oil in 5 $\frac{3}{4}$ hours.
2600' oil in 7 $\frac{3}{4}$ hours.
2700' oil in 9 $\frac{3}{4}$ hours.