WELL LOG BUREAU - KANSAS GEOLOGICAL SOCIETY
412 Union National Bk Bldg., Wichita, Kansas

33-5-20W


15-147-00537

CITIES SERVICE OIL CO.
Kohlman No. 1.

SEC.33 T.5 R. 20 W
SW NW NE
990'S 330'E of N¼ Cor.

Total Depth. 3570'
Comm. 9-13-42 Comp. 10-14-42
Shot or Treated. None
Contractor. Harbar Drlg.Co.
Issued. 1-2-43

County. Phillips



CASING:
8 5/8" 162' Cem.
5 1/2" 3552' Cem.

Elevation. 2170

Production. Phy.Pot.400 BO, No wtr

Figures Indicate Bottom of Formations.

shale & shells	0-170
shale	300
chalky lime	330
shale & shells	795
sand & shale brks	1048
shale	1080
anhydrite	1140
shale, shells, sand	1232
sand	1400
sand & shale	1560
shale	1620
shale & shells	1688
anhydrite & lime	1705
shale & brkn lime	1905
shale & shells	2010
shale & lime	2055
shale & shells	2200
shale & lime	2295
lime	2345
lime & shale	2390
shale	2486
shale & lime	2610
lime & shale	2655
lime brkn	2720
lime & shale	2785
brkn lime & shale	2840
shale & lime	3070
shale	3078
lime	3108
shale & lime	3232
lime	3271
lime & shale	3330
chert & lime	3335
lime	3357
lime & shale	3378
lime	3405
lime cherty hd	3447
lime	3510
shale & lime	3543
lime sdy	3549
lime	3550
lime sdy	3556
cored sand(no rec.)	3558
3558 Rot.TD=3558 SLM	
sand hd	3561
sand	3570
Total Depth.	

10-12-42 Temporary Phy. Pot.89 oil, no wtr, 24 hrs
10-13 & 14 - Deepened 3558-70

Top Reagan 3550
Penetration 20

Fillup:
600' oil in 4 hrs at 3558
2400' oil in 12½ hrs at 3558
2600' oil in 17½ hrs at 3558