

34-5-21W

CITIES SERVICE OIL CO.
 Muir No. 1.

SEC 34 T. 5 R. 21 W
 SW¹/₄ NW
 330' N 330' E of W¹/₄ cor.

Total Depth. 3788
 Comm. 12-6-41 Comp. 12-22-41
 Shot or Treated. None.
 Contractor. Twin Drilling Co.
 Issued. 2-7-42

County Norton.



CASING.

85/8" 212" cemented.

Elevation.

Production. DRY.

Figures Indicate Bottom of Formations.

surface and sand	20	lime grey hard	3725
shale and shells	100	lime grey med	3780
sand soft	125	lime and shale	3770
shale and shells	212	granite wash	3787
shale blue	575	granite	3788
shale and shells	590	Total Depth.	
iron and shale	605		
shale blue and shells	840	TOBS	
sand and hard shells	1038	Lansing	3438
sand and shells	1100	Arbuckle	3697
shale and shells	1223	Granite Wash	3749
sdv shale soft	1275	Granite	3387
shale and lime shells	1420	Penetration	1'
sand light soft	1553		
sand grey med	1585		
shale chalk & anhydrite	1665		
shale red and shells	1753		
shale and shells	1845		
lime light med	1900		
lime and shale breaks	2108		
shale and shells	2473		
shale and lime shells	2530		
lime grey hard	2600		
shale and shells	2710		
lime grey hard	2725		
lime and shale breaks	2745		
lime grey hard	2896		
shale breaks and lime	3315		
shale and shells	3340		
lime light hard	3382		
lime grey hard	3523		
lime light med	3538		
chert and lime hard	3545		
lime and shale breaks	3648		
sdv shale soft	3654		
shale and lime shells	3670		
lime and shale breaks	3680		
lime and shale	3711		